


| | | |
|---|--------------------------|---------------------------------|
|  | SAFETY DATA SHEET | Page : 1/14 |
| | | Revised edition no : 1 |
| | | Compilation date : 3 / 7 / 2018 |
| | | Supersedes : 3 / 2 / 2016 |
| Acetylene | | NOAL_0001 |
| | | Country : DK / Language : EN |

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : Acetylene, Flamal Acetylene, Alphagaz 1 Acetylene, Altop Acetylene, Albee Flame Ace
 SDS no : NOAL_0001
 Chemical description : Acetylene (dissolved)
 CAS-No. : 74-86-2
 EC-No. : 200-816-9
 EC Index-No. : 601-015-00-0
 Registration-No. : 01-2119457406-36
 Chemical formula : C2H2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional. Perform risk assessment prior to use.
 See the list of identified uses and exposure scenarios in the annex of the safety data sheet.
 Contact supplier for more information on uses.
 Uses advised against : Consumer use.

1.3. Details of the supplier of the safety data sheet

Company identification

AIR LIQUIDE Denmark A/S
 Høje Taastrupvej 42
 2630 Taastrup - DENMARK
 T +45 76 25 25 25
eunordic-sds@airliquide.com

E-Mail address (competent person) : eunordic-sds@airliquide.com

1.4. Emergency telephone number

Emergency telephone number : 112
 Availability
 (24 / 7)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture


Classification according to Regulation (EC) No. 1272/2008 [CLP]

| | | |
|------------------|---------------------------------------|------|
| Physical hazards | Flammable gases, Category 1 | H220 |
| | Chemically Unstable gases, Category A | H230 |
| | Gases under pressure : Dissolved gas | H280 |


2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) : Danger
 Hazard statements (CLP) : H220 - Extremely flammable gas..
 H230 - May react explosively even in the absence of air..

| | | |
|---|--------------------------|---------------------------------|
|  | SAFETY DATA SHEET | Page : 2/14 |
| | | Revised edition no : 1 |
| | | Compilation date : 3 / 7 / 2018 |
| | | Supersedes : 3 / 2 / 2016 |
| Acetylene | | NOAL_0001 |
| | | Country : DK / Language : EN |

H280 - Contains gas under pressure; may explode if heated..

Precautionary statements (CLP)

- Prevention : P202 - Do not handle until all safety precautions have been read and understood..
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking..
- Response : P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely..
P381 - In case of leakage, eliminate all ignition sources..
- Storage : P403 - Store in a well-ventilated place..

2.3. Other hazards

: None.

SECTION 3: Composition/information on ingredients

3.1. Substances

| Name | Product identifier | Composition [V-%]: | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|-----------------------|---|--------------------|--|
| Acetylene (dissolved) | (CAS-No.) 74-86-2 (EC-No.) 200-816-9 (EC Index-No.) 601-015-00-0 (Registration-No.) 01-2119457406-36 | 100 | Flam. Gas 1, H220 Chem. Unst. Gas A, H230 Press. Gas (Diss.), H280 |

For safety reasons, the acetylene is dissolved in acetone (Flam. Liq. 2, Eye Irrit. 2, STOT SE 3) or dimethylformamide (Flam.Liq.3, Repr. 1B, Acute Tox. 4, Eye Irrit. 2) in the gas receptacle. Vapour of the solvent is carried away as impurity when the acetylene is extracted from the gas receptacle. The concentration of the solvent vapour in the gas is lower than the concentration limits to change the classification of the acetylene. The cylinder contains a porous material which in some cases contains asbestos fibres. The asbestos fibres are encapsulated in the solid porous material and are not released under normal conditions of use. See section 13 for the disposal of those cylinders. Dimethylformamide is on the Candidate List of Substances of Very High Concern (SVHC) that might be subject to authorization for future placing on the market and uses.

Contains no other components or impurities which will influence the classification of the product.

3.2. Mixtures : Not established.

SECTION 4: First aid measures

4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
- Skin contact : Adverse effects not expected from this product.
- Eye contact : Adverse effects not expected from this product.
- Ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

: Refer to section 11.

4.3. Indication of any immediate medical attention and special treatment needed


: None.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog.
Dry powder.
- Unsuitable extinguishing media : Carbon dioxide.
Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

| | | |
|---|--------------------------|---------------------------------|
|  | SAFETY DATA SHEET | Page : 3/14 |
| | | Revised edition no : 1 |
| | | Compilation date : 3 / 7 / 2018 |
| | | Supersedes : 3 / 2 / 2016 |
| Acetylene | | NOAL_0001 |
| | | Country : DK / Language : EN |

Specific hazards : Exposure to fire may cause containers to rupture/explode.
Hazardous combustion products : Carbon monoxide.

5.3. Advice for firefighters

Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.
If possible, stop flow of product.
Use water spray or fog to knock down fire fumes if possible.
Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Extinguish any other fire.
Continue water spray from protected position until container stays cool.
Move containers away from the fire area if this can be done without risk.

Special protective equipment for fire fighters : In confined space use self-contained breathing apparatus.
Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

: Try to stop release.
Evacuate area.
Monitor concentration of released product.
Consider the risk of potentially explosive atmospheres.
Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.
Eliminate ignition sources.
Ensure adequate air ventilation.
Act in accordance with local emergency plan.
Stay upwind.

6.2. Environmental precautions

: Try to stop release.

6.3. Methods and material for containment and cleaning up


: Ventilate area.

6.4. Reference to other sections

: See also sections 8 and 13.


SECTION 7: Handling and storage

7.1. Precautions for safe handling

| | | |
|---|--------------------------|--|
|  | SAFETY DATA SHEET | Page : 4/14 |
| | | Revised edition no : 1 |
| | | Compilation date : 3 / 7 / 2018 |
| | | Supersedes : 3 / 2 / 2016 |
| Acetylene | | NOAL_0001 Country : DK / Language : EN |

- Safe use of the product : The product must be handled in accordance with good industrial hygiene and safety procedures.
- Only experienced and properly instructed persons should handle gases under pressure.
 - Consider pressure relief device(s) in gas installations.
 - Ensure the complete gas system was (or is regularly) checked for leaks before use.
 - Do not smoke while handling product.
 - Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.
 - Avoid suck back of water, acid and alkalis.
 - Assess the risk of potentially explosive atmospheres and the need for explosion-proof equipment.
 - Purge air from system before introducing gas.
 - Take precautionary measures against static discharge.
 - Keep away from ignition sources (including static discharges).
 - Consider the use of only non-sparking tools.
 - Avoid contact with pure copper, mercury, silver and brass with greater than 65% copper.
 - Operating pressure in piping should be limited to 1.5 bar (gauge) or less due to more stringent national regulations (with maximum diameter DN25).
 - Consider the use of flash back arrestors.
 - Solvent may accumulate in piping systems. For maintenance activities use appropriate resistant gloves, assess the necessity to use a respiratory filter device (specify gloves and filters for DMF or acetone use) and wear safety goggles. Avoid breathing the vapour of the solvent. Provide adequate ventilation.
 - For further information on safe use refer to EIGA code of practice acetylene (EIGA Doc 123).
 - Do not breathe gas.
 - Avoid release of product into atmosphere.
 - Ensure equipment is adequately earthed.
- Safe handling of the gas receptacle : Refer to supplier's container handling instructions.
- Do not allow backfeed into the container.
 - Protect cylinders from physical damage; do not drag, roll, slide or drop.
 - When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.
 - Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.
 - If user experiences any difficulty operating cylinder valve discontinue use and contact supplier.
 - Never attempt to repair or modify container valves or safety relief devices.
 - Damaged valves should be reported immediately to the supplier.
 - Keep container valve outlets clean and free from contaminants particularly oil and water.
 - Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.
 - Close container valve after each use and when empty, even if still connected to equipment.
 - Never attempt to transfer gases from one cylinder/container to another.
 - Never use direct flame or electrical heating devices to raise the pressure of a container.
 - Do not remove or deface labels provided by the supplier for the identification of the cylinder contents.
 - Suck back of water into the container must be prevented.
 - Open valve slowly to avoid pressure shock.

7.2. Conditions for safe storage, including any incompatibilities

| | | |
|---|--------------------------|---------------------------------|
|  | SAFETY DATA SHEET | Page : 5/14 |
| | | Revised edition no : 1 |
| | | Compilation date : 3 / 7 / 2018 |
| | | Supersedes : 3 / 2 / 2016 |
| Acetylene | | NOAL_0001 |
| | | Country : DK / Language : EN |

- : Observe all regulations and local requirements regarding storage of containers.
- Containers should not be stored in conditions likely to encourage corrosion.
- Container valve guards or caps should be in place.
- Containers should be stored in the vertical position and properly secured to prevent them from falling over.
- Stored containers should be periodically checked for general condition and leakage.
- Keep container below 50°C in a well ventilated place.
- Store containers in location free from fire risk and away from sources of heat and ignition.
- Keep away from combustible materials.
- Segregate from oxidant gases and other oxidants in store.
- All electrical equipment in the storage areas should be compatible with the risk of a potentially explosive atmosphere.

7.3. Specific end use(s)

: None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

OEL (Occupational Exposure Limits) : No data available.

| Acetylene (dissolved) (74-86-2) | |
|--|------------------------------------|
| DNEL: Derived no effect level (Workers) | |
| Acute - systemic effects, inhalation | 2675 mg/m ³ 2500 ppm |
| Long-term - systemic effects, inhalation | 2675 mg/m ³ 2500 ppm |

PNEC (Predicted No-Effect Concentration) : No data available.

8.2. Exposure controls


8.2.1. Appropriate engineering controls

- : Provide adequate general and local exhaust ventilation.
- Product to be handled in a closed system.
- Systems under pressure should be regularly checked for leakages.
- Ensure exposure is below occupational exposure limits (where available).
- Gas detectors should be used when flammable gases/vapours may be released.
- Consider the use of a work permit system e.g. for maintenance activities.

8.2.2. Individual protection measures, e.g. personal protective equipment

- : A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered:
PPE compliant to the recommended EN/ISO standards should be selected.

- Eye/face protection : Wear safety glasses with side shields.
Standard EN 166 - Personal eye-protection - specifications.
- Skin protection
 - Hand protection : Wear working gloves when handling gas containers.
Standard EN 388 - Protective gloves against mechanical risk.
 - Other : Consider the use of flame resistant anti-static safety clothing.
Standard EN ISO 14116 - Limited flame spread materials.
Standard EN ISO 1149-5 - Protective clothing: Electrostatic properties.
Wear safety shoes while handling containers.
Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
- Respiratory protection : Gas filters may be used if all surrounding conditions e.g. type and concentration of the contaminant(s) and duration of use are known.
Use gas filters with full face mask, where exposure limits may be exceeded for a short-term period, e.g. connecting or disconnecting containers.
Gas filters do not protect against oxygen deficiency.
Standard EN 14387 - Gas filter(s), combined filter(s) and full face mask - EN 136.

| | | |
|---|--------------------------|--|
|  | SAFETY DATA SHEET | Page : 6/14 |
| | | Revised edition no : 1 |
| | | Compilation date : 3 / 7 / 2018 |
| | | Supersedes : 3 / 2 / 2016 |
| Acetylene | | NOAL_0001 Country : DK / Language : EN |

• Thermal hazards : Wear goggles with suitable filter lenses when use is cutting/welding.

8.2.3. Environmental exposure controls

: Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

- Physical state at 20°C / 101.3kPa : Gas.
- Colour : Colourless.

Odour : Garlic like. Poor warning properties at low concentrations.

Odour threshold : Odour threshold is subjective and inadequate to warn of overexposure.

pH value : Not applicable for gases and gas mixtures.

Molar mass : 26 g/mol

Melting point : -80.8 °C

Boiling point : -84 °C

Flash point : Not applicable for gases and gas mixtures.

Critical temperature [°C] : 35 °C

Evaporation rate (ether=1) : Not applicable for gases and gas mixtures.

Flammability range : 2.3 - 100 vol %

Vapour pressure [20°C] : 44 bar(a)

Vapour pressure [50°C] : Not applicable.

Relative density, gas (air=1) : 0.9

Relative density, liquid (water=1) : Not applicable.

Solubility in water : 1185 mg/l

Partition coefficient n-octanol/water [log Kow] : 0.37

Auto-ignition temperature : 305 °C

Decomposition point [°C] : Not applicable.

Viscosity [20°C] : No reliable data available.

Explosive Properties : Not applicable.

Oxidising Properties : Not applicable.

9.2. Other information

Other data : No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

: No reactivity hazard other than the effects described in sub-sections below.


10.2. Chemical stability

: Dissolved in a solvent supported in a porous mass.
Stable under recommended handling and storage conditions (see section 7).
May react explosively even in the absence of air.

10.3. Possibility of hazardous reactions

: Can form explosive mixture with air.
May react violently with oxidants.
May react explosively even in the absence of air.
May decompose violently at high temperature and/or pressure or in the presence of a catalyst.

10.4. Conditions to avoid

| | | |
|---|--------------------------|---------------------------------|
|  | SAFETY DATA SHEET | Page : 7/14 |
| | | Revised edition no : 1 |
| | | Compilation date : 3 / 7 / 2018 |
| | | Supersedes : 3 / 2 / 2016 |
| Acetylene | | NOAL_0001 |
| | | Country : DK / Language : EN |

: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
 High temperature.
 High pressure.
 Avoid moisture in installation systems.

10.5. Incompatible materials

: Air, Oxidisers.
 Forms explosive acetylides with copper, silver and mercury.
 Do not use alloys containing more than 65% copper.
 Do not use alloys containing more than 43% silver.
 For additional information on compatibility refer to ISO 11114.

10.6. Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Acetylene has low inhalation toxicity, the LOAEC for mild intoxication in humans with no residual effects is 100 000ppm (107,000 mg/m3).
 There are no data on oral and dermal toxicity (studies are not technically feasible as the substance is a gas at room temperature).

Skin corrosion/irritation : No known effects from this product.

Serious eye damage/irritation : No known effects from this product.

Respiratory or skin sensitisation : No known effects from this product.

Germ cell mutagenicity : No known effects from this product.

Carcinogenicity : No known effects from this product.

Reproductive toxicity : No known effects from this product.
 No known effects from this product.

STOT-single exposure : No known effects from this product.

STOT-repeated exposure : No known effects from this product.

Aspiration hazard : Not applicable for gases and gas mixtures.

SECTION 12: Ecological information

12.1. Toxicity

Assessment : Classification criteria are not met.

EC50 48h - Daphnia magna [mg/l] : 242 mg/l

EC50 72h - Algae [mg/l] : 57 mg/l

LC50 96 h - Fish [mg/l] : 545 mg/l

12.2. Persistence and degradability


Assessment : Will rapidly degrade by indirect photolysis in air.
 Will not undergo hydrolysis.

12.3. Bioaccumulative potential

Assessment : Not expected to bioaccumulate due to the low log Kow (log Kow < 4).
 Refer to section 9.

12.4. Mobility in soil

Assessment : Because of its high volatility, the product is unlikely to cause ground or water pollution.
 Partition into soil is unlikely.

| | | |
|---|--------------------------|---------------------------------|
|  | SAFETY DATA SHEET | Page : 8/14 |
| | | Revised edition no : 1 |
| | | Compilation date : 3 / 7 / 2018 |
| | | Supersedes : 3 / 2 / 2016 |
| Acetylene | | NOAL_0001 |
| | | Country : DK / Language : EN |

12.5. Results of PBT and vPvB assessment

Assessment : Not classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects : No known effects from this product.
Effect on the ozone layer : None.
Effect on global warming : No known effects from this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Contact supplier if guidance is required.
Do not discharge into any place where its accumulation could be dangerous.
Ensure that the emission levels from local regulations or operating permits are not exceeded.
Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org> for more guidance on suitable disposal methods.
Return unused product in original cylinder to supplier.
List of hazardous waste codes (from Commission Decision 2001/118/EC) : 16 05 04 *: Gases in pressure containers (including halons) containing dangerous substances.

13.2. Additional information

: Dispose of cylinder via gas supplier only. Cylinder contains a porous material which in some cases contains asbestos fibres and is saturated with a solvent (acetone or dimethylformamide). External treatment and disposal of waste should comply with applicable local and/or national regulations.

SECTION 14: Transport information

14.1. UN number

UN-No. : 1001

14.2. UN proper shipping name

Transport by road/rail (ADR/RID) : ACETYLENE, DISSOLVED
Transport by air (ICAO-TI / IATA-DGR) : Acetylene, dissolved
Transport by sea (IMDG) : ACETYLENE, DISSOLVED

14.3. Transport hazard class(es)

Labelling :



2.1 : Flammable gases.

Transport by road/rail (ADR/RID)

Class : 2.
Classification code : 4F.
Hazard identification number : 239.
Tunnel Restriction : B/D - Tank carriage : Passage forbidden through tunnels of category B, C, D and E. Other carriage : Passage forbidden through tunnels of category D and E.


Transport by air (ICAO-TI / IATA-DGR)

Class / Div. (Sub. risk(s)) : 2.1

Transport by sea (IMDG)

Class / Div. (Sub. risk(s)) : 2.1
Emergency Schedule (EmS) - Fire : F-D.
Emergency Schedule (EmS) - Spillage : S-U.

14.4. Packing group

| | | |
|---|--------------------------|--|
|  | SAFETY DATA SHEET | Page : 9/14 |
| | | Revised edition no : 1 |
| | | Compilation date : 3 / 7 / 2018 |
| | | Supersedes : 3 / 2 / 2016 |
| Acetylene | | NOAL_0001 Country : DK / Language : EN |

Transport by road/rail (ADR/RID) : Not established.
Transport by air (ICAO-TI / IATA-DGR) : Not established.
Transport by sea (IMDG) : Not established.

14.5. Environmental hazards

Transport by road/rail (ADR/RID) : None.
Transport by air (ICAO-TI / IATA-DGR) : None.
Transport by sea (IMDG) : None.

14.6. Special precautions for user

Packing Instruction(s)

Transport by road/rail (ADR/RID) : P200.
Transport by air (ICAO-TI / IATA-DGR)
Passenger and Cargo Aircraft : Forbidden.
Cargo Aircraft only : 200.
Transport by sea (IMDG) : P200.

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment.
Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.
Before transporting product containers:
- Ensure there is adequate ventilation.
- Ensure that containers are firmly secured.
- Ensure cylinder valve is closed and not leaking.
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure valve protection device (where provided) is correctly fitted.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

: Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

Restrictions on use : None.
Seveso Directive : 2012/18/EU (Seveso III) : Listed.

National regulations

National legislation : Ensure all national/local regulations are observed.

Denmark


Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product

15.2. Chemical safety assessment

A CSA has been carried out.

SECTION 16: Other information

Indication of changes : Revised safety data sheet in accordance with commission regulation (EU) No 453/2010.

| | | |
|---|--------------------------|---------------------------------|
|  | SAFETY DATA SHEET | Page : 10/14 |
| | | Revised edition no : 1 |
| | | Compilation date : 3 / 7 / 2018 |
| | | Supersedes : 3 / 2 / 2016 |
| Acetylene | | NOAL_0001 |
| | | Country : DK / Language : EN |


Abbreviations and acronyms : ATE - Acute Toxicity Estimate
 CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
 REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
 EINECS - European Inventory of Existing Commercial Chemical Substances
 CAS# - Chemical Abstract Service number
 PPE - Personal Protection Equipment
 LC50 - Lethal Concentration to 50 % of a test population
 RMM - Risk Management Measures
 PBT - Persistent, Bioaccumulative and Toxic
 vPvB - Very Persistent and Very Bioaccumulative
 STOT- SE : Specific Target Organ Toxicity - Single Exposure
 CSA - Chemical Safety Assessment
 EN - European Standard
 UN - United Nations
 ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
 IATA - International Air Transport Association
 IMDG code - International Maritime Dangerous Goods
 RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
 WGK - Water Hazard Class
 STOT - RE : Specific Target Organ Toxicity - Repeated Exposure

Training advice : Ensure operators understand the flammability hazard.

Full text of H- and EUH-statements

| | |
|--------------------|---|
| Chem. Unst. Gas A | Chemically Unstable gases, Category A |
| Flam. Gas 1 | Flammable gases, Category 1 |
| Press. Gas (Diss.) | Gases under pressure : Dissolved gas |
| H220 | Extremely flammable gas. |
| H230 | May react explosively even in the absence of air. |
| H280 | Contains gas under pressure; may explode if heated. |

DISCLAIMER OF LIABILITY : Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.
 Details given in this document are believed to be correct at the time of going to press.
 Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

| | | |
|---|---|--|
|  | <h1 style="margin: 0;">SAFETY DATA SHEET</h1> | Page : 11/14 |
| | | Revised edition no : 1 |
| | | Compilation date : 3 / 7 / 2018 |
| | | Supersedes : 3 / 2 / 2016 |
| <h2 style="margin: 0;">Acetylene</h2> | | NOAL_0001 Country : DK / Language : EN |

1. Exposure scenario EIGA001-1

Industrial uses, closed contained conditions

| |
|---|
| ES Ref.: EIGA001-1 ES Type: Worker - EIGA Revision date: 01/10/2016 |
|---|

| | |
|--------------------------------------|--|
| Use descriptors | SU0, SU8, SU9, SU17 PROC1, PROC2, PROC3, PROC8b, PROC9 ERC1, ERC2, ERC4, ERC6a, ERC6b, ERC7, ERC8d |
| Processes, tasks, activities covered | Industrial uses, including product transfers and associated laboratory activities within different closed or contained systems |
| Assessment method | ECETOC TRA 2.0 |

2. Operational conditions and risk management measures

1.2.1 Contributing scenario controlling environmental exposure (ERC1, ERC2, ERC4, ERC6a, ERC6b, ERC7, ERC8d)

| | |
|---|--|
| Manufacture of substances, Formulation of preparations, Industrial use of processing aids in processes and products, not becoming part of articles, Industrial use resulting in manufacture of another substance (use of intermediates), Industrial use of reactive processing aids, Industrial use of substances in closed systems, Wide dispersive outdoor use of processing aids in open systems | |
| ERC1 | Manufacture of substances |
| ERC2 | Formulation of preparations |
| ERC4 | Industrial use of processing aids in processes and products, not becoming part of articles |
| ERC6a | Industrial use resulting in manufacture of another substance (use of intermediates) |
| ERC6b | Industrial use of reactive processing aids |
| ERC7 | Industrial use of substances in closed systems |
| ERC8d | Wide dispersive outdoor use of processing aids in open systems |

Product characteristics

| | |
|---------------------------------------|---|
| Physical form of product | See section 9 of the SDS, No additional information |
| Concentration of substance in product | <= 100 % |

Operational conditions

| | | |
|---|--|-----|
| Amounts used | The actual tonnage handled per site is not considered to influence the immissions as such for this scenario as there is practically no release | |
| Frequency and duration of use | Emission Days (days/year) | 260 |
| Environmental factors not influenced by risk management | No additional information | |

Risk Management Measures

| | | |
|---|---|--|
| Organisation measures to prevent/limit release from site | Ensure operatives are trained to minimise releases | |
| Conditions and measures related to sewage treatment plant | Wastewater emission controls are not applicable as there is no direct release to wastewater | |
| Conditions and measures related to external treatment of waste for disposal | See section 13 of the SDS | |

1.2.2 Contributing scenario controlling worker exposure (PROC1, PROC2, PROC3, PROC8b, PROC9)


| | |
|--|--|
| Use in closed process, no likelihood of exposure, Use in closed, continuous process with occasional controlled exposure, Use in closed batch process (synthesis or formulation), Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities, Transfer of substance or preparation into small containers (dedicated filling line, including weighing) | |
| PROC1 | Use in closed process, no likelihood of exposure |
| PROC2 | Use in closed, continuous process with occasional controlled exposure |
| PROC3 | Use in closed batch process (synthesis or formulation) |
| PROC8b | Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities |
| PROC9 | Transfer of substance or mixture into small containers (dedicated filling line, including weighing) |

Product characteristics

| | |
|---------------------------------------|---|
| Physical form of product | See section 9 of the SDS, No additional information |
| Concentration of substance in product | <= 100 % |

Operational conditions

| | | |
|--------------|---|--|
| Amounts used | The actual tonnage handled per shift is not | |
|--------------|---|--|

| | | |
|---|--------------------------|---------------------------------|
|  | SAFETY DATA SHEET | Page : 12/14 |
| | | Revised edition no : 1 |
| | | Compilation date : 3 / 7 / 2018 |
| | | Supersedes : 3 / 2 / 2016 |
| Acetylene | | NOAL_0001 |
| | | Country : DK / Language : EN |

| | | |
|---|--|-------------|
| | considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential. | |
| Frequency and duration of use | Exposure duration | <= 8 h/day |
| | Covers frequency up to: | 5 days/week |
| Other given operational conditions affecting workers exposure | Indoor or outdoor use | |

Risk Management Measures

| | | |
|---|---|--|
| Technical conditions and measures at process level (source) to prevent release | See section 7 of the SDS. | |
| | Handle product within a closed system | |
| | Apply a good standard of general or controlled ventilation when maintenance activities are carried out. | |
| Organisational measures to prevent /limit releases, dispersion and exposure | Ensure operatives are trained to minimise exposure | |
| | Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed | |
| Conditions and measures related to personal protection, hygiene and health evaluation | See section 8 of the SDS. | |

3. Exposure estimation and reference to its source

3.1. Health

3.2. Environment


4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

4.1. Health

| | |
|-------------------|--|
| Guidance - Health | Check that RMMs and OCs are as described above or of equivalent efficiency |
|-------------------|--|

4.2. Environment

| | |
|------------------------|--|
| Guidance - Environment | Check that RMMs and OCs are as described above or of equivalent efficiency |
|------------------------|--|

| | | |
|---|---|--|
|  | <h1 style="margin: 0;">SAFETY DATA SHEET</h1> | Page : 13/14 |
| | | Revised edition no : 1 |
| | | Compilation date : 3 / 7 / 2018 |
| | | Supersedes : 3 / 2 / 2016 |
| <h2 style="margin: 0;">Acetylene</h2> | | NOAL_0001 Country : DK / Language : EN |

1. Exposure scenario EIGA001-2

Professional uses

| |
|---|
| ES Ref.: EIGA001-2 ES Type: Worker - EIGA Revision date: 01/10/2016 |
|---|

| | |
|--------------------------------------|---|
| Use descriptors | SU17 PROC4, PROC8a ERC1, ERC9a, ERC9b |
| Processes, tasks, activities covered | Professional uses, including transfer of product in non-industrial settings |
| Assessment method | ECETOC TRA 2.0 |

2. Operational conditions and risk management measures

1.2.1 Contributing scenario controlling environmental exposure (ERC9a, ERC9b)

| | |
|---|---|
| Wide dispersive indoor use of substances in closed systems, Wide dispersive outdoor use of substances in closed systems | |
| ERC9a | Wide dispersive indoor use of substances in closed systems |
| ERC9b | Wide dispersive outdoor use of substances in closed systems |

Product characteristics

| | |
|---------------------------------------|---|
| Physical form of product | See section 9 of the SDS, No additional information |
| Concentration of substance in product | <= 100 % |

Operational conditions

| | |
|---|--|
| Amounts used | No additional information |
| Other given operational conditions affecting environmental exposure | Closed systems are used in order to prevent unintended emissions |

Risk Management Measures

| | |
|---|--|
| Organisation measures to prevent/limit release from site | Ensure operatives are trained to minimise exposure |
| Conditions and measures related to sewage treatment plant | No additional information |
| Conditions and measures related to external treatment of waste for disposal | See section 13 of the SDS |

1.2.2 Contributing scenario controlling worker exposure (PROC4, PROC8a)

| | |
|--|--|
| Use in batch and other process (synthesis) where opportunity for exposure arises, Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non dedicated facilities | |
| PROC4 | Use in batch and other process (synthesis) where opportunity for exposure arises |
| PROC8a | Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non dedicated facilities |

Product characteristics


| | |
|---------------------------------------|---|
| Physical form of product | See section 9 of the SDS, No additional information |
| Concentration of substance in product | <= 100 % |

Operational conditions

| | | |
|---|--|-------------|
| Amounts used | The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential. | |
| Frequency and duration of use | Exposure duration | <= 8 h/day |
| | Covers frequency up to: | 5 days/week |
| Other given operational conditions affecting workers exposure | Indoor or outdoor use | |

Risk Management Measures

| | |
|--|---|
| Technical conditions and measures at process level (source) to prevent release | Handle product within a closed system |
| | Apply a good standard of general or controlled ventilation when maintenance activities are carried out. |
| | See section 7 of the SDS. |

| | | |
|---|--------------------------|---------------------------------|
|  | SAFETY DATA SHEET | Page : 14/14 |
| | | Revised edition no : 1 |
| | | Compilation date : 3 / 7 / 2018 |
| | | Supersedes : 3 / 2 / 2016 |
| Acetylene | | NOAL_0001 |
| | | Country : DK / Language : EN |

| | | |
|---|---|--|
| Organisational measures to prevent /limit releases, dispersion and exposure | Ensure operatives are trained to minimise exposure | |
| | Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed | |
| Conditions and measures related to personal protection, hygiene and health evaluation | See section 8 of the SDS. | |

3. Exposure estimation and reference to its source

3.1. Health

3.2. Environment

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

4.1. Health

| | |
|-------------------|--|
| Guidance - Health | Check that RMMs and OCs are as described above or of equivalent efficiency |
|-------------------|--|

4.2. Environment

| | |
|------------------------|--|
| Guidance - Environment | Check that RMMs and OCs are as described above or of equivalent efficiency |
|------------------------|--|