

Ammonia, anhydrous**NOAL_0002**

Country : FI / Language : EN

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Trade name : Ammonia, anhydrous, Ammonia, Ammonia N38, Ammonia HG, Ammonia LGC
SDS no : NOAL_0002
Chemical description : Ammonia, anhydrous
CAS-No. : 7664-41-7
EC-No. : 231-635-3
EC Index-No. : 007-001-00-5
Registration-No. : 01-2119488876-14
Chemical formula : NH₃

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional uses. Perform risk assessment prior to use.
See the list of identified uses and exposure scenarios in the annex of the safety data sheet.
Contact supplier for more information on uses.
Uses advised against : Consumer use.

1.3. Details of the supplier of the safety data sheet**Company identification**

Air Liquide Finland Oy
Yrtpellontie 1 C 3 krs.
90230 OULU - FINLAND
T +353 20 779 0580
eunordic-sds@airliquide.com

E-Mail address (competent person) : eunordic-sds@airliquide.com

1.4. Emergency telephone number

Emergency telephone number : FI: Myrkytystietokeskus: 09-471 977 (suora) tai 09-4711 (vaihe) / EN: Poison Information Centre: 09-471 977 (direct) or 09-4711 (switchboard)
Availability
(24 / 7)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Physical hazards	Flammable gases, Category 2	H221
	Gases under pressure : Liquefied gas	H280
Health hazards	Acute toxicity (inhalation:gas) Category 3	H331
	Skin corrosion/irritation, Category 1B	H314
	Serious eye damage/eye irritation, Category 1	H318
Environmental hazards	Hazardous to the aquatic environment — Acute Hazard, Category 1	H400
	Hazardous to the aquatic environment — Chronic Hazard, Category 2	H411

2.2. Label elements**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



GHS04



GHS05



GHS06



GHS09

Ammonia, anhydrous

NOAL_0002

Country : FI / Language : EN

Signal word (CLP) : Danger

Hazard statements (CLP) : H280 - Contains gas under pressure; may explode if heated.
 H331 - Toxic if inhaled.
 H410 - Very toxic to aquatic life with long lasting effects.
 H221 - Flammable gas.
 H314 - Causes severe skin burns and eye damage.
 EUH071 - Corrosive to the respiratory tract.

Precautionary statements (CLP)

- Prevention : P273 - Avoid release to the environment.
 P260 - Do not breathe gas, vapours.
 P280 - Wear protective gloves, protective clothing, eye protection, face protection.
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Response : P303+P361+P353+P315 - IF ON SKIN : (or hair) Take off immediately all contaminated clothing. Rinse skin with water or shower. Get immediate medical advice.
 P304+P340+P315 - IF INHALED : Remove person to fresh air and keep comfortable for breathing. Get immediate medical advice.
 P305+P351+P338+P315 - IF IN EYES : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice.
 P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
 P381 - In case of leakage, eliminate all ignition sources.
- Storage : P405 - Store locked up.
 P403 - Store in a well-ventilated place.

2.3. Other hazards

: None.

SECTION 3: Composition/information on ingredients

3.1. Substances

Name	Product identifier	Composition [V-%]:	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Ammonia, anhydrous	(CAS-No.) 7664-41-7 (EC-No.) 231-635-3 (EC Index-No.) 007-001-00-5 (Registration-No.) 01-2119488876-14	100	Flam. Gas 2, H221 Press. Gas (Liq.), H280 Acute Tox. 3 (Inhalation:gas), H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400 Aquatic Chronic 2, H411

Contains no other components or impurities which will influence the classification of the product.

3.2. Mixtures : Not applicable.

SECTION 4: First aid measures

4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.
- Skin contact : Remove contaminated clothing. Drench affected area with water for at least 15 minutes. In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.
- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes.
- Ingestion : Ingestion is not considered a potential route of exposure.

Ammonia, anhydrous**NOAL_0002**

Country : FI / Language : EN

4.2. Most important symptoms and effects, both acute and delayed

- : May cause severe chemical burns to skin and cornea. Suitable first-aid treatment should be immediately available. Seek medical advice before using product.
- Prolonged exposure to small concentrations may result in pulmonary oedema.
- Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.
- Refer to section 11.

4.3. Indication of any immediate medical attention and special treatment needed

- : Obtain medical assistance.
- Treat with corticosteroid spray as soon as possible after inhalation.

SECTION 5: Firefighting measures**5.1. Extinguishing media**

- Suitable extinguishing media : Water spray or fog.
Foam.
- Unsuitable extinguishing media : Carbon dioxide.
Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

- Specific hazards : Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products : Nitric oxide/nitrogen dioxide.

5.3. Advice for firefighters

- Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.
If possible, stop flow of product.
Use water spray or fog to knock down fire fumes if possible.
Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Extinguish any other fire.
Move containers away from the fire area if this can be done without risk.
- Special protective equipment for fire fighters : Wear gas tight chemically protective clothing in combination with self contained breathing apparatus.
Standard EN 943-2: Protective clothing against liquid and gaseous chemicals, aerosols and solid particles. Gas-tight chemical protective suits for emergency teams.
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

- : Try to stop release.
Evacuate area.
Monitor concentration of released product.
Consider the risk of potentially explosive atmospheres.
Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.
Eliminate ignition sources.
Use chemically protective clothing.
Ensure adequate air ventilation.
Act in accordance with local emergency plan.
Stay upwind.

6.2. Environmental precautions

Ammonia, anhydrous**NOAL_0002**

Country : FI / Language : EN

- : Reduce vapour with fog or fine water spray.
Try to stop release.

6.3. Methods and material for containment and cleaning up

- : Hose down area with water.
Ventilate area.
Keep area evacuated and free from ignition sources until any spilled liquid has evaporated (ground free from frost).
Wash contaminated equipment or sites of leaks with copious quantities of water.

6.4. Reference to other sections

- : See also sections 8 and 13.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Safe use of the product

- : Do not breathe gas.
Avoid release of product into atmosphere.
The product must be handled in accordance with good industrial hygiene and safety procedures.
Only experienced and properly instructed persons should handle gases under pressure.
Consider pressure relief device(s) in gas installations.
Ensure the complete gas system was (or is regularly) checked for leaks before use.
Do not smoke while handling product.
Avoid exposure, obtain special instructions before use.
Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.
Installation of a cross purge assembly between the container and the regulator is recommended.
Purge system with dry inert gas (e.g. helium or nitrogen) before gas is introduced and when system is placed out of service.
Avoid suck back of water, acid and alkalis.
Assess the risk of potentially explosive atmospheres and the need for explosion-proof equipment.
Purge air from system before introducing gas.
Take precautionary measures against static discharge.
Keep away from ignition sources (including static discharges).
Consider the use of only non-sparking tools.
Ensure equipment is adequately earthed.

Safe handling of the gas receptacle

- : Refer to supplier's container handling instructions.
Do not allow backfeed into the container.
Protect containers from physical damage; do not drag, roll, slide or drop.
When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.
Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.
If user experiences any difficulty operating valve discontinue use and contact supplier.
Never attempt to repair or modify container valves or safety relief devices.
Damaged valves should be reported immediately to the supplier.
Keep container valve outlets clean and free from contaminants particularly oil and water.
Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.
Close container valve after each use and when empty, even if still connected to equipment.
Never attempt to transfer gases from one cylinder/container to another.
Never use direct flame or electrical heating devices to raise the pressure of a container.
Do not remove or deface labels provided by the supplier for the identification of the content of

Ammonia, anhydrous

NOAL_0002

Country : FI / Language : EN

the container.

Suck back of water into the container must be prevented.

Open valve slowly to avoid pressure shock.

7.2. Conditions for safe storage, including any incompatibilities

- : Observe all regulations and local requirements regarding storage of containers.
- Containers should not be stored in conditions likely to encourage corrosion.
- Container valve guards or caps should be in place.
- Containers should be stored in the vertical position and properly secured to prevent them from falling over.
- Stored containers should be periodically checked for general condition and leakage.
- Keep container below 50°C in a well ventilated place.
- Store containers in location free from fire risk and away from sources of heat and ignition.
- Keep away from combustible materials.
- Segregate from oxidant gases and other oxidants in store.
- All electrical equipment in the storage areas should be compatible with the risk of a potentially explosive atmosphere.

7.3. Specific end use(s)

- : None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ammonia, anhydrous (7664-41-7)	
EU - Occupational Exposure Limits	
Local name	Ammonia, anhydrous
IOELV TWA (mg/m ³)	14 mg/m ³
IOELV TWA (ppm)	20 ppm
IOELV STEL (mg/m ³)	36 mg/m ³
IOELV STEL (ppm)	50 ppm
Finland - Occupational Exposure Limits	
Local name	Vedetön ammoniakki
HTP-arvo (8h) (mg/m ³)	14 mg/m ³
HTP-arvo (8h) (ppm)	20 ppm
HTP-arvo (15 min)	36 mg/m ³
HTP-arvo (15 min) (ppm)	50 ppm
Ammonia, anhydrous (7664-41-7)	
EU - Occupational Exposure Limits	
Local name	Ammonia, anhydrous
IOELV TWA (mg/m ³)	14 mg/m ³
IOELV TWA (ppm)	20 ppm
IOELV STEL (mg/m ³)	36 mg/m ³
IOELV STEL (ppm)	50 ppm
Finland - Occupational Exposure Limits	
Local name	Vedetön ammoniakki
HTP-arvo (8h) (mg/m ³)	14 mg/m ³
HTP-arvo (8h) (ppm)	20 ppm
HTP-arvo (15 min)	36 mg/m ³
HTP-arvo (15 min) (ppm)	50 ppm

Ammonia, anhydrous (7664-41-7)	
DNEL: Derived no effect level (Workers)	
Acute - local effects, inhalation	36 mg/m ³
Acute - systemic effects, inhalation	47.6 mg/m ³
Long-term - local effects, inhalation	14 mg/m ³
Long-term - systemic effects, inhalation	47.6 mg/m ³
Acute - systemic effects, dermal	6.8 mg/kg bw/day
Long-term - systemic effects, dermal	6.8 mg/kg bw/day

Ammonia, anhydrous

NOAL_0002

Country : FI / Language : EN

Ammonia, anhydrous (7664-41-7)	
DNEL: Derived no effect level (Workers)	
Acute - local effects, inhalation	36 mg/m ³
Acute - systemic effects, inhalation	47.6 mg/m ³
Long-term - local effects, inhalation	14 mg/m ³
Long-term - systemic effects, inhalation	47.6 mg/m ³
Acute - systemic effects, dermal	6.8 mg/kg bw/day
Long-term - systemic effects, dermal	6.8 mg/kg bw/day

Ammonia, anhydrous (7664-41-7)	
PNEC: Predicted no effect concentration	
Aqua (freshwater)	0.0011 mg/l
Aqua (marine water)	0.0011 mg/l

Ammonia, anhydrous (7664-41-7)	
PNEC: Predicted no effect concentration	
Aqua (freshwater)	0.0011 mg/l
Aqua (marine water)	0.0011 mg/l

8.2. Exposure controls

8.2.1. Appropriate engineering controls

- : Provide adequate general and local exhaust ventilation.
- Product to be handled in a closed system.
- Systems under pressure should be regularly checked for leakages.
- Ensure exposure is below occupational exposure limits (where available).
- Gas detectors should be used when toxic gases may be released.
- Consider the use of a work permit system e.g. for maintenance activities.

8.2.2. Individual protection measures, e.g. personal protective equipment

- : A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered:
PPE compliant to the recommended EN/ISO standards should be selected.
- Eye/face protection
 - : Wear goggles and a face shield when transfilling or breaking transfer connections.
 - Standard EN 166 - Personal eye-protection - specifications.
 - Provide readily accessible eye wash stations and safety showers.
- Skin protection
 - Hand protection
 - : Wear working gloves when handling gas containers.
 - Standard EN 388 - Protective gloves against mechanical risk.
 - Wear cold insulating gloves when transfilling or breaking transfer connections.
 - Standard EN 511 - Cold insulating gloves.
 - Wear chemically resistant protective gloves.
 - Standard EN 374 - Protective gloves against chemicals.
 - Permeation time: minimum >30min short term exposure: material / thickness Chloroprene rubber (Neoprene®) (CR) / 0.5 [mm].
 - Permeation time: minimum >480min long term exposure : material / thickness Butyl rubber (IIR) / 0.7 [mm].
 - Consult glove manufacturer's product information on material suitability and material thickness.
 - The breakthrough time of the selected gloves must be greater than the intended use period.
 - Other
 - : Keep suitable chemically resistant protective clothing readily available for emergency use.
 - Standard EN943-1 - Full protective suits against liquid, solid and gaseous chemicals.
 - Wear safety shoes while handling containers.
 - Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
- Respiratory protection
 - : Gas filters may be used if all surrounding conditions e.g. type and concentration of the contaminant(s) and duration of use are known.
 - Use gas filters with full face mask, where exposure limits may be exceeded for a short-term period, e.g. connecting or disconnecting containers.
 - Recommended: Filter K (green).
 - Gas filters do not protect against oxygen deficiency.
 - Standard EN 14387 - Gas filter(s), combined filter(s) and standard EN136, full face masks .

Ammonia, anhydrous**NOAL_0002**

Country : FI / Language : EN

Keep self contained breathing apparatus readily available for emergency use.
Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems.
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.

• Thermal hazards : None in addition to the above sections.

8.2.3. Environmental exposure controls

: Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance

• Physical state at 20°C / 101.3kPa	: Gas
• Colour	: Colourless.
Odour	: Ammoniacal.
Odour threshold	: Odour threshold is subjective and inadequate to warn of overexposure.
pH	: If dissolved in water pH-value will be affected.
Melting point / Freezing point	: -77.7 °C
Boiling point	: -33 °C
Flash point	: Not applicable for gases and gas mixtures.
Evaporation rate	: Not applicable for gases and gas mixtures.
Flammability (solid, gas)	: Flammable gas.
Explosive limits	: 15.4 - 33.6 vol %
Vapour pressure [20°C]	: 8.6 bar(a)
Vapour pressure [50°C]	: 20 bar(a)
Vapour density	: Not applicable.
Relative density, liquid (water=1)	: 0.7
Relative density, gas (air=1)	: 0.6
Water solubility	: 517 g/l
Partition coefficient n-octanol/water (Log Kow)	: Not applicable for inorganic products.
Auto-ignition temperature	: 630 °C
Decomposition temperature	: Not applicable.
Viscosity	: No reliable data available.
Explosive properties	: Not applicable.
Oxidising properties	: Not applicable.

9.2. Other information

Molar mass	: 17 g/mol
Critical temperature [°C]	: 132 °C

SECTION 10: Stability and reactivity**10.1. Reactivity**

: No reactivity hazard other than the effects described in sub-sections below.

Ammonia, anhydrous**NOAL_0002**

Country : FI / Language : EN

10.2. Chemical stability

: Stable under normal conditions.

10.3. Possibility of hazardous reactions: Can form explosive mixture with air.
May react violently with oxidants.**10.4. Conditions to avoid**: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
Avoid moisture in installation systems.**10.5. Incompatible materials**: Air, Oxidisers.
Reacts with water to form corrosive alkalis.
May react violently with acids.
For additional information on compatibility refer to ISO 11114.**10.6. Hazardous decomposition products**

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**: Toxic if inhaled.
Inhalation of large amounts leads to bronchospasm, laryngeal oedema and pseudomembrane formation.

LC50 Inhalation - Rat [ppm]

2000 ppm/4h

Ammonia, anhydrous (7664-41-7)

LC50 Inhalation - Rat [ppm]

2000 ppm/4h

Skin corrosion/irritation

: Causes severe skin burns and eye damage.

Serious eye damage/irritation

: Causes serious eye damage.

Respiratory or skin sensitisation

: No known effects from this product.

Germ cell mutagenicity

: No known effects from this product.

Carcinogenicity

: No known effects from this product.

Reproductive toxicity

:

Toxic for reproduction : Fertility

: No known effects from this product.

Toxic for reproduction : unborn child

: No known effects from this product.

STOT-single exposure: Severe corrosion to the respiratory tract at high concentrations.
May cause inflammation of the respiratory system.**Target organ(s)**

: Respiratory tract.

STOT-repeated exposure

: No known effects from this product.

Aspiration hazard

: Not applicable for gases and gas mixtures.

SECTION 12: Ecological information**12.1. Toxicity****Assessment**: Very toxic to aquatic life.
Toxic to aquatic life with long lasting effects.

EC50 48h - Daphnia magna [mg/l]

: 101 mg/l

Ammonia, anhydrous**NOAL_0002**

Country : FI / Language : EN

EC50 72h - Algae [mg/l] : No data available.

LC50 96 h - Fish [mg/l] : 0.89 mg/l

Ammonia, anhydrous (7664-41-7)

EC50 48h - Daphnia magna [mg/l] : 101 mg/l

EC50 72h - Algae [mg/l] : No data available.

LC50 96 h - Fish [mg/l] : 0.89 mg/l

12.2. Persistence and degradability

Assessment : The substance is readily biodegradable. Unlikely to persist.

12.3. Bioaccumulative potential

Assessment : No data available.

12.4. Mobility in soilAssessment : Because of its high volatility, the product is unlikely to cause ground or water pollution.
Partition into soil is unlikely.**12.5. Results of PBT and vPvB assessment**

Assessment : Not classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects : May cause pH changes in aqueous ecological systems.

Effect on the ozone layer : None.

Effect on global warming : No known effects from this product.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Contact supplier if guidance is required.

Must not be discharged to atmosphere.

Toxic and corrosive gases formed during combustion should be scrubbed before discharge to atmosphere.

Gas may be scrubbed in sulphuric acid solution.

Gas may be scrubbed in water.

Ensure that the emission levels from local regulations or operating permits are not exceeded.

Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org> for more guidance on suitable disposal methods.

Return unused product in original container to supplier.

List of hazardous waste codes (from Commission Decision 2000/532/EC as amended)

: 16 05 04 *: Gases in pressure containers (including halons) containing hazardous substances.

13.2. Additional information

: External treatment and disposal of waste should comply with applicable local and/or national regulations.

SECTION 14: Transport information**14.1. UN number**

UN-No. : 1005

Ammonia, anhydrous

NOAL_0002

Country : FI / Language : EN

14.2. UN proper shipping name

Transport by road/rail (ADR/RID) : AMMONIA, ANHYDROUS

Transport by air (ICAO-TI / IATA-DGR) : Ammonia, anhydrous

Transport by sea (IMDG) : AMMONIA, ANHYDROUS

14.3. Transport hazard class(es)

Labelling



2.3 : Toxic gases.

8 : Corrosive substances.

Environmentally hazardous substances

Transport by road/rail (ADR/RID)

Class : 2
 Classification code : 2TC
 Hazard identification number : 268
 Tunnel Restriction : C/D - Tank carriage : Passage forbidden through tunnels of category C, D and E. Other carriage : Passage forbidden through tunnels of category D and E

Transport by sea (IMDG)

Class / Div. (Sub. risk(s)) : 2.3 (8)
 Emergency Schedule (EmS) - Fire : F-C
 Emergency Schedule (EmS) - Spillage : S-U

14.4. Packing group

Transport by road/rail (ADR/RID) : Not established.
 Transport by air (ICAO-TI / IATA-DGR) : Not established.
 Transport by sea (IMDG) : Not established.

14.5. Environmental hazards

Transport by road/rail (ADR/RID) : Environmentally hazardous substance / mixture.
 Transport by air (ICAO-TI / IATA-DGR) : Environmentally hazardous substance / mixture.
 Transport by sea (IMDG) : Marine pollutant

14.6. Special precautions for user

Packing Instruction(s)

Transport by road/rail (ADR/RID) : P200
 Transport by air (ICAO-TI / IATA-DGR)
 Passenger and Cargo Aircraft : Forbidden.
 Cargo Aircraft only : Forbidden.
 Transport by sea (IMDG) : P200

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment.
 Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.
 Before transporting product containers:
 - Ensure there is adequate ventilation.
 - Ensure that containers are firmly secured.
 - Ensure valve is closed and not leaking.
 - Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
 - Ensure valve protection device (where provided) is correctly fitted.

Ammonia, anhydrous

NOAL_0002

Country : FI / Language : EN

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

: Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

Restrictions on use : None.

Seveso Directive : 2012/18/EU (Seveso III) : Listed.

National regulations

National legislation : Ensure all national/local regulations are observed.

15.2. Chemical safety assessment

: A CSA has been carried out.

SECTION 16: Other information

Indication of changes : Revised safety data sheet in accordance with commission regulation (EU) No 453/2010.

Abbreviations and acronyms : ATE - Acute Toxicity Estimate
 CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
 REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
 EINECS - European Inventory of Existing Commercial Chemical Substances
 CAS# - Chemical Abstract Service number
 PPE - Personal Protection Equipment
 LC50 - Lethal Concentration to 50 % of a test population
 RMM - Risk Management Measures
 PBT - Persistent, Bioaccumulative and Toxic
 vPvB - Very Persistent and Very Bioaccumulative
 STOT- SE : Specific Target Organ Toxicity - Single Exposure
 CSA - Chemical Safety Assessment
 EN - European Standard
 UN - United Nations
 ADR - International Agreement concerning the International Carriage of Dangerous Goods by Road
 IATA - International Air Transport Association
 IMDG code - International Maritime Dangerous Goods
 RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
 WGK - Water Hazard Class
 STOT - RE : Specific Target Organ Toxicity - Repeated Exposure

Training advice : Users of breathing apparatus must be trained.
 Ensure operators understand the flammability hazard.
 Ensure operators understand the toxicity hazard.

Full text of H- and EUH-statements

Acute Tox. 3 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 3
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2

Ammonia, anhydrous**NOAL_0002**

Country : FI / Language : EN

Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Gas 2	Flammable gases, Category 2
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
H221	Flammable gas.
H280	Contains gas under pressure; may explode if heated
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H400	Very toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

DISCLAIMER OF LIABILITY

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

Details given in this document are believed to be correct at the time of going to press.

Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

Ammonia, anhydrous**NOAL_0002**

Country : FI / Language : EN

Annex to the safety data sheet

This Annex documents the Exposure Scenarios (ESs) related to the identified uses of the registered substance. The ESs detail protective measures for workers and the environment in addition to those described in sections 7, 8, 11, 12 and 13 of the SDS that are required to ensure that the potential exposure to workers and the environment remains within acceptable levels for each of the identified uses.

Table of contents of the Annex

Identified Uses	Es N°	Short title	Page
Water treatment	EIGA00 2-1	Industrial uses, closed contained conditions	14
Formulation of mixtures in pressure receptacles	EIGA00 2-1	Industrial uses, closed contained conditions	14
Transfilling in pressure receptacles	EIGA00 2-1	Industrial uses, closed contained conditions	14
Metal treatment	EIGA00 2-1	Industrial uses, closed contained conditions	14
Electronic component manufacture	EIGA00 2-1	Industrial uses, closed contained conditions	14
Manufacture of pharmaceutical products	EIGA00 2-1	Industrial uses, closed contained conditions	14
Calibration of analysis equipment	EIGA00 2-1	Industrial uses, closed contained conditions	14
Feedstock in chemical processes	EIGA00 2-1	Industrial uses, closed contained conditions	14
Precursor for fertiliser/explosive manufacture	EIGA00 2-1	Industrial uses, closed contained conditions	14
Exhaust gas DeNOx applications	EIGA00 2-1	Industrial uses, closed contained conditions	14
Treatment of plastics	EIGA00 2-1	Industrial uses, closed contained conditions	14
Aluminium casting	EIGA00 2-1	Industrial uses, closed contained conditions	14
Treatment of textiles	EIGA00 2-1	Industrial uses, closed contained conditions	14
Waste recycling	EIGA00 2-1	Industrial uses, closed contained conditions	14
Refilling of refrigeration equipment	EIGA00 2-2	Professional uses	24
In photocopying machines	EIGA00 2-2	Professional uses	24
Reaction gas in mass spectrometry	EIGA00 2-2	Professional uses	24
Microfiche developing and duplication	EIGA00 2-2	Professional uses	24

Ammonia, anhydrous

NOAL_0002

Country : FI / Language : EN

1. EIGA002-1: Industrial uses, closed contained conditions

1.1. Title section

Industrial uses, closed contained conditions

ES Ref.: EIGA002-1

Revision date: 01/07/2016

Processes, tasks, activities covered	Industrial uses, including product transfers and associated laboratory activities within different closed or contained systems
Environment	Use descriptors
CS1	ERC1
CS2	ERC2
CS3	ERC4
CS4	ERC6a
CS5	ERC6b
CS6	ERC7
Worker	Use descriptors
CS7	PROC1
CS8	PROC2
CS9	PROC3
CS10	PROC4
CS11	PROC8b
CS12	PROC9
Assessment method	ECETOC TRA 2.0 EUSES

1.2. Conditions of use affecting exposure

1.2.1. Control of environmental exposure: ERC1

ERC1	Manufacture of substances
------	---------------------------

Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	<= 100 %

Amount used, frequency and duration of use (or from service life)

Annual site tonnage:	950000 t/yr
Regional use tonnage:	6500000 t/yr
Emission Days (days/year)	330

Technical and organisational conditions and measures

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.	
Soil emission controls are not applicable as there is no direct release to soil	
Ensure operatives are trained to minimise releases	

Conditions and measures related to sewage treatment plant

Direct emissions to the municipal STP should not be made.	
---	--

Conditions and measures related to treatment of waste (including article waste)

See section 13 of the SDS	
---------------------------	--

Other conditions affecting environmental exposure

Closed systems are used in order to prevent unintended emissions	
Flow rate of receiving water at least:	18000 m ³ /d
Dilution of STP emissions at least:	10

1.2.2. Control of environmental exposure: ERC2

ERC2	Formulation of preparations
------	-----------------------------

Ammonia, anhydrous

NOAL_0002

Country : FI / Language : EN

Product (article) characteristics	
Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	<= 100 %
Amount used, frequency and duration of use (or from service life)	
Annual site tonnage:	1000000 t/yr
Regional use tonnage:	3800000 t/yr
Emission Days (days/year)	330
Technical and organisational conditions and measures	
Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.	
Soil emission controls are not applicable as there is no direct release to soil	
Ensure operatives are trained to minimise releases	
Conditions and measures related to sewage treatment plant	
Direct emissions to the municipal STP should not be made.	
Conditions and measures related to treatment of waste (including article waste)	
See section 13 of the SDS	
Other conditions affecting environmental exposure	
Closed systems are used in order to prevent unintended emissions	
Flow rate of receiving water at least:	18000 m ³ /d
Dilution of STP emissions at least:	10
1.2.3. Control of environmental exposure: ERC4	
ERC4	Industrial use of processing aids in processes and products, not becoming part of articles
Product (article) characteristics	
Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	<= 100 %
Amount used, frequency and duration of use (or from service life)	
Annual site tonnage:	25000 t/yr
Regional use tonnage:	354000 t/yr
Emission Days (days/year)	330
Technical and organisational conditions and measures	
Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.	
Soil emission controls are not applicable as there is no direct release to soil	
Ensure operatives are trained to minimise releases	
Conditions and measures related to sewage treatment plant	
Direct emissions to the municipal STP should not be made.	
Conditions and measures related to treatment of waste (including article waste)	
See section 13 of the SDS	
Other conditions affecting environmental exposure	
Closed systems are used in order to prevent unintended emissions	
Flow rate of receiving water at least:	18000 m ³ /d
Dilution of STP emissions at least:	10
1.2.4. Control of environmental exposure: ERC6a	
ERC6a	Industrial use resulting in manufacture of another substance (use of intermediates)
Product (article) characteristics	
Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	<= 100 %

Ammonia, anhydrous

NOAL_0002

Country : FI / Language : EN

Amount used, frequency and duration of use (or from service life)	
Annual site tonnage:	800000 t/yr
Regional use tonnage:	3800000 t/yr
Emission Days (days/year)	330

Technical and organisational conditions and measures	
Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.	
Soil emission controls are not applicable as there is no direct release to soil	
Ensure operatives are trained to minimise releases	

Conditions and measures related to sewage treatment plant	
Direct emissions to the municipal STP should not be made.	

Conditions and measures related to treatment of waste (including article waste)	
See section 13 of the SDS	

Other conditions affecting environmental exposure	
Closed systems are used in order to prevent unintended emissions	
Flow rate of receiving water at least:	18000 m ³ /d
Dilution of STP emissions at least:	10

1.2.5. Control of environmental exposure: ERC6b

ERC6b	Industrial use of reactive processing aids
-------	--

Product (article) characteristics	
Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	<= 100 %

Amount used, frequency and duration of use (or from service life)	
Annual site tonnage:	25000 t/yr
Regional use tonnage:	354000 t/yr
Emission Days (days/year)	330

Technical and organisational conditions and measures	
Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.	
Soil emission controls are not applicable as there is no direct release to soil	
Ensure operatives are trained to minimise releases	

Conditions and measures related to sewage treatment plant	
Direct emissions to the municipal STP should not be made.	

Conditions and measures related to treatment of waste (including article waste)	
See section 13 of the SDS	

Other conditions affecting environmental exposure	
Closed systems are used in order to prevent unintended emissions	
Flow rate of receiving water at least:	18000 m ³ /d
Dilution of STP emissions at least:	10

1.2.6. Control of environmental exposure: ERC7

ERC7	Industrial use of substances in closed systems
------	--

Product (article) characteristics	
Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	<= 100 %

Amount used, frequency and duration of use (or from service life)	
Annual site tonnage:	25000 t/yr
Regional use tonnage:	354000 t/yr

Ammonia, anhydrous

NOAL_0002

Country : FI / Language : EN

Emission Days (days/year)	330
---------------------------	-----

Technical and organisational conditions and measures

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.

Soil emission controls are not applicable as there is no direct release to soil

Ensure operatives are trained to minimise releases

Conditions and measures related to sewage treatment plant

Direct emissions to the municipal STP should not be made.

Conditions and measures related to treatment of waste (including article waste)

See section 13 of the SDS

Other conditions affecting environmental exposure

Closed systems are used in order to prevent unintended emissions

 Flow rate of receiving water at least: 18000 m³/d

Dilution of STP emissions at least: 10

1.2.7. Control of worker exposure: PROC1

PROC1	Use in closed process, no likelihood of exposure
-------	--

Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
--------------------------	---

Concentration of substance in product	<= 100 %
---------------------------------------	----------

Amount used (or contained in articles), frequency and duration of use/exposure

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.

Exposure duration	<= 8 h/day
-------------------	------------

Covers frequency up to:	5 days/week
-------------------------	-------------

Technical and organisational conditions and measures

Handle product within a closed system

Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

Ensure operatives are trained to minimise exposure

Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

Conditions and measures related to personal protection, hygiene and health evaluation

See section 8 of the SDS.

Other conditions affecting workers exposure

Indoor or outdoor use

1.2.8. Control of worker exposure: PROC2

PROC2	Use in closed, continuous process with occasional controlled exposure
-------	---

Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
--------------------------	---

Concentration of substance in product	<= 100 %
---------------------------------------	----------

Amount used (or contained in articles), frequency and duration of use/exposure

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.

Exposure duration	<= 8 h/day
-------------------	------------

Ammonia, anhydrous

NOAL_0002

Country : FI / Language : EN

Covers frequency up to:	5 days/week
-------------------------	-------------

Technical and organisational conditions and measures

Handle product within a closed system	
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.	
Ensure samples are obtained under containment or extract ventilation.	
Drain down and flush system prior to equipment break-in or maintenance.	
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable face shield. Wear suitable coveralls to prevent exposure to the skin	Personal protection measures have to be applied in case of potential exposure only.
Wear gloves providing a minimum efficiency of (%):	90
Wear a respirator providing a minimum efficiency of (%):	95 Mandatory if activities take place outdoors or indoors with no local exhaust ventilation
See section 8 of the SDS.	

Other conditions affecting workers exposure

Indoor or outdoor use

1.2.9. Control of worker exposure: PROC3

PROC3	Use in closed batch process (synthesis or formulation)
-------	--

Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	<= 100 %

Amount used (or contained in articles), frequency and duration of use/exposure

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.	
Exposure duration	<= 8 h/day
Covers frequency up to:	5 days/week

Technical and organisational conditions and measures

Handle product within a closed system	
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.	
Ensure samples are obtained under containment or extract ventilation.	
Drain down and flush system prior to equipment break-in or maintenance.	
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable face shield. Wear suitable coveralls to prevent exposure to the skin	Personal protection measures have to be applied in case of potential exposure only.
Wear gloves providing a minimum efficiency of (%):	90
Wear a respirator providing a minimum efficiency of (%):	95 Mandatory if activities take place outdoors or indoors with no local exhaust ventilation
See section 8 of the SDS.	

Other conditions affecting workers exposure

Indoor or outdoor use

Ammonia, anhydrous

NOAL_0002

Country : FI / Language : EN

1.2.10. Control of worker exposure: PROC4

PROC4	Use in batch and other process (synthesis) where opportunity for exposure arises
-------	--

Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	<= 100 %

Amount used (or contained in articles), frequency and duration of use/exposure

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.	
Exposure duration	<= 8 h/day
Covers frequency up to:	5 days/week

Technical and organisational conditions and measures

Handle product within a closed system	
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.	
Ensure samples are obtained under containment or extract ventilation.	
Drain down and flush system prior to equipment break-in or maintenance.	
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable face shield. Wear suitable coveralls to prevent exposure to the skin	Personal protection measures have to be applied in case of potential exposure only.
Wear gloves providing a minimum efficiency of (%):	90
Wear a respirator providing a minimum efficiency of (%):	95 Mandatory if activities take place outdoors or indoors with no local exhaust ventilation
See section 8 of the SDS.	

Other conditions affecting workers exposure

Indoor or outdoor use	
-----------------------	--

1.2.11. Control of worker exposure: PROC8b

PROC8b	Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities
--------	--

Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	<= 100 %

Amount used (or contained in articles), frequency and duration of use/exposure

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.	
Exposure duration	<= 8 h/day
Covers frequency up to:	5 days/week

Technical and organisational conditions and measures

Handle product within a closed system	
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.	
Fill containers at dedicated fill points supplied with local extract ventilation.	
Drain down and flush system prior to equipment break-in or maintenance.	
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.	

Ammonia, anhydrous

NOAL_0002

Country : FI / Language : EN

Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable face shield. Wear suitable coveralls to prevent exposure to the skin	Personal protection measures have to be applied in case of potential exposure only.
Wear gloves providing a minimum efficiency of (%):	90
Wear a respirator providing a minimum efficiency of (%):	95 Mandatory if activities take place outdoors or indoors with no local exhaust ventilation
See section 8 of the SDS.	

Other conditions affecting workers exposure

Indoor or outdoor use	
-----------------------	--

1.2.12. Control of worker exposure: PROC9

PROC9	Transfer of substance or mixture into small containers (dedicated filling line, including weighing)
-------	---

Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	<= 100 %

Amount used (or contained in articles), frequency and duration of use/exposure

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.	
Exposure duration	<= 8 h/day
Covers frequency up to:	5 days/week

Technical and organisational conditions and measures

Handle product within a closed system	
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.	
Fill containers at dedicated fill points supplied with local extract ventilation.	
Drain down and flush system prior to equipment break-in or maintenance.	
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable face shield. Wear suitable coveralls to prevent exposure to the skin	Personal protection measures have to be applied in case of potential exposure only.
Wear gloves providing a minimum efficiency of (%):	90
Wear a respirator providing a minimum efficiency of (%):	95 Mandatory if activities take place outdoors or indoors with no local exhaust ventilation
See section 8 of the SDS.	

Other conditions affecting workers exposure

Indoor or outdoor use	
-----------------------	--

1.3. Exposure estimation and reference to its source

1.3.1. Environmental release and exposure: ERC1

Assessment method		EUSES			
Protection target	Unit	Exposure estimation	PNEC	RCR	Assessment conditions
Freshwater	mg/l	0.000133	0.0011	0.121	
Marine water	mg/l	0.0000315	0.0011	0.029	

Ammonia, anhydrous

NOAL_0002

Country : FI / Language : EN

1.3.2. Environmental release and exposure: ERC2

Assessment method		EUSES			
Protection target	Unit	Exposure estimation	PNEC	RCR	Assessment conditions
Freshwater	mg/l	0.0000497	0.0011	0.045	
Marine water	mg/l	0.000012	0.0011	0.011	

1.3.3. Environmental release and exposure: ERC4

Protection target	Unit	Exposure estimation	PNEC	RCR	Assessment conditions
Freshwater	mg/l	0.0000108	0.0011	0.01	
Marine water	mg/l	0.0000231	0.0011	0.021	

1.3.4. Environmental release and exposure: ERC6a

Assessment method		EUSES			
Protection target	Unit	Exposure estimation	PNEC	RCR	Assessment conditions
Freshwater	mg/l	0.0000837	0.0011	0.076	
Marine water	mg/l	0.0000205	0.0011	0.019	

1.3.5. Environmental release and exposure: ERC6b

Protection target	Unit	Exposure estimation	PNEC	RCR	Assessment conditions
Freshwater	mg/l	0.00000173	0.0011	0.002	
Marine water	mg/l	0.00000019	0.0011	≈ 0.00018	

1.3.6. Environmental release and exposure: ERC7

Protection target	Unit	Exposure estimation	PNEC	RCR	Assessment conditions
Freshwater	mg/l	0.00000558	0.0011	0.005	
Marine water	mg/l	0.00000121	0.0011	0.001	

1.3.7. Worker exposure: PROC1

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Dermal - Long-term - systemic effects	0.34 mg/kg bodyweight/day	Outdoor use, Indoor use , Without LEV, No gloves worn	0.05
Inhalation - Long-term - systemic effects	0 mg/m ³	Outdoor use, Indoor use , Without LEV	< 0.01
Dermal - Acute - systemic effects	0.34 mg/kg bodyweight/day	Outdoor use, Indoor use , Without LEV, No gloves worn	0.05
Inhalation - Acute - systemic effects	0 mg/m ³	Outdoor use, Indoor use , Without LEV	< 0.01
Acute - Local - Inhalation	0 mg/m ³	Outdoor use, Indoor use , Without LEV	< 0.01
Long term - Local - Inhalation	0 mg/m ³	Outdoor use, Indoor use , Without LEV	< 0.01

1.3.8. Worker exposure: PROC2

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Dermal - Long-term - systemic effects	1.37 mg/kg bodyweight/day	Outdoor use, Indoor use , Without LEV, No gloves worn	0.201
	0.14 mg/kg bodyweight/day	Indoor use , With LEV, No gloves worn	0.021
Inhalation - Long-term - systemic effects	1.24 mg/m ³	Outdoor use, With RPE xx%95%	0.026
	3.54 mg/m ³	Indoor use , With LEV, No RPE	0.074
Dermal - Acute - systemic effects	1.37 mg/kg bodyweight/day	Outdoor use, Indoor use , Without LEV, No gloves worn	0.201
	0.14 mg/kg bodyweight/day	Indoor use , With LEV, No gloves worn	0.021
Inhalation - Acute - systemic	1.24 mg/m ³	Outdoor use, With RPE xx%95%	0.026

Ammonia, anhydrous

NOAL_0002

Country : FI / Language : EN

effects	3.54 mg/m ³	Indoor use , With LEV, No RPE	0.074
Acute - Local - Inhalation	1.24 mg/m ³	Outdoor use, With RPE xx%95%	0.034
	3.54 mg/m ³	Indoor use , With LEV, No RPE	0.098
Long term - Local - Inhalation	1.24 mg/m ³	Outdoor use, With RPE xx%95%	0.089
	3.54 mg/m ³	Indoor use , With LEV, No RPE	0.253

1.3.9. Worker exposure: PROC3

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Dermal - Long-term - systemic effects	0.34 mg/kg bodyweight/day	Outdoor use, Indoor use , Without LEV, No gloves worn	0.05
	0.03 mg/kg bodyweight/day	Indoor use , With LEV, No gloves worn	0.004
Inhalation - Long-term - systemic effects	2.48 mg/m ³	Outdoor use, With RPE xx%95%	0.052
	7.08 mg/m ³	Indoor use , With LEV, No RPE	0.149
Dermal - Acute - systemic effects	0.34 mg/kg bodyweight/day	Outdoor use, Indoor use , Without LEV, No gloves worn	0.05
	0.03 mg/kg bodyweight/day	Indoor use , With LEV, No gloves worn	0.004
Inhalation - Acute - systemic effects	2.48 mg/m ³	Outdoor use, With RPE xx%95%	0.052
	7.08 mg/m ³	Indoor use , With LEV, No RPE	0.149
Acute - Local - Inhalation	2.48 mg/m ³	Outdoor use, With RPE xx%95%	0.069
	7.08 mg/m ³	Indoor use , With LEV, No RPE	0.197
Long term - Local - Inhalation	2.48 mg/m ³	Outdoor use, With RPE xx%95%	0.177
	7.08 mg/m ³	Indoor use , With LEV, No RPE	0.506

1.3.10. Worker exposure: PROC4

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Dermal - Long-term - systemic effects	0.69 mg/kg bodyweight/day	Outdoor use, Indoor use , Without LEV, Gloves worn (90% Reduction)	0.101
	0.69 mg/kg bodyweight/day	Indoor use , With LEV, No gloves worn	0.101
Inhalation - Long-term - systemic effects	2.48 mg/m ³	Outdoor use, With RPE xx%95%	0.052
	7.08 mg/m ³	Indoor use , With LEV, No RPE	0.149
Dermal - Acute - systemic effects	0.69 mg/kg bodyweight/day	Outdoor use, Indoor use , Without LEV, Gloves worn (90% Reduction)	0.101
	0.69 mg/kg bodyweight/day	Indoor use , With LEV, No gloves worn	0.101
Inhalation - Acute - systemic effects	2.48 mg/m ³	Outdoor use, With RPE xx%95%	0.052
	7.08 mg/m ³	Indoor use , With LEV, No RPE	0.149
Acute - Local - Inhalation	2.48 mg/m ³	Outdoor use, With RPE xx%95%	0.069
	7.08 mg/m ³	Indoor use , With LEV, No RPE	0.197
Long term - Local - Inhalation	2.48 mg/m ³	Outdoor use, With RPE xx%95%	0.177
	7.08 mg/m ³	Indoor use , With LEV, No RPE	0.506

1.3.11. Worker exposure: PROC8b

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Dermal - Long-term - systemic effects	0.69 mg/kg bodyweight/day	Outdoor use, Indoor use , Without LEV, Gloves worn (90% Reduction)	0.101
	0.69 mg/kg bodyweight/day	Indoor use , With LEV, No gloves worn	0.101
Inhalation - Long-term - systemic effects	3.72 mg/m ³	Outdoor use, With RPE xx%95%	0.078
	3.19 mg/m ³	Indoor use , With LEV, No RPE	0.067
Dermal - Acute - systemic effects	0.69 mg/kg bodyweight/day	Outdoor use, Indoor use , Without LEV, Gloves worn (90% Reduction)	0.101
	0.69 mg/kg bodyweight/day	Indoor use , With LEV, No gloves worn	0.101
Inhalation - Acute - systemic effects	3.72 mg/m ³	Outdoor use, With RPE xx%95%	0.078
	3.19 mg/m ³	Indoor use , With LEV, No RPE	0.067
Acute - Local - Inhalation	3.72 mg/m ³	Outdoor use, With RPE xx%95%	0.103
	3.19 mg/m ³	Indoor use , With LEV, No RPE	0.089
Long term - Local - Inhalation	3.72 mg/m ³	Outdoor use, With RPE xx%95%	0.266

Ammonia, anhydrous

NOAL_0002

Country : FI / Language : EN

3.19 mg/m³

Indoor use , With LEV, No RPE

0.228

1.3.12. Worker exposure: PROC9

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Dermal - Long-term - systemic effects	0.69 mg/kg bodyweight/day	Outdoor use, Indoor use , Without LEV, Gloves worn (90% Reduction)	0.101
	0.69 mg/kg bodyweight/day	Indoor use , With LEV, No RPE	0.101
Inhalation - Long-term - systemic effects	4.96 mg/m ³	Outdoor use, With RPE xx%95%	0.104
	0.71 mg/m ³	Indoor use , With LEV, With RPE xx%	0.015
Dermal - Acute - systemic effects	0.69 mg/kg bodyweight/day	Outdoor use, Indoor use , Without LEV, Gloves worn (90% Reduction)	0.101
	0.69 mg/kg bodyweight/day	Indoor use , With LEV, No RPE	0.101
Inhalation - Acute - systemic effects	4.96 mg/m ³	Outdoor use, With RPE xx%95%	0.104
	0.71 mg/m ³	Indoor use , With LEV, With RPE xx%	0.015
Acute - Local - Inhalation	4.96 mg/m ³	Outdoor use, With RPE xx%95%	0.138
	0.71 mg/m ³	Indoor use , With LEV, With RPE xx%	0.02
Long term - Local - Inhalation	4.96 mg/m ³	Outdoor use, With RPE xx%95%	0.354
	0.71 mg/m ³	Indoor use , With LEV, With RPE xx%	0.051

1.4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

1.4.1. Environment

Guidance - Environment	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see :
------------------------	--

1.4.2. Health

Guidance - Health	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see :
-------------------	--

Ammonia, anhydrous

NOAL_0002

Country : FI / Language : EN

2. EIGA002-2: Professional uses

2.1. Title section

Professional uses

ES Ref.: EIGA002-2

Revision date: 01/07/2016

Processes, tasks, activities covered	Professional uses, including transfer of product in non-industrial settings
Environment	Use descriptors
CS1	ERC9a, ERC9b
Worker	Use descriptors
CS2	PROC4
CS3	PROC8a
Assessment method	ECETOC TRA 2.0

2.2. Conditions of use affecting exposure

2.2.1. Control of environmental exposure: ERC9a, ERC9b

ERC9a	Wide dispersive indoor use of substances in closed systems
ERC9b	Wide dispersive outdoor use of substances in closed systems

Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	<= 100 %

Amount used, frequency and duration of use (or from service life)

No additional information	
---------------------------	--

Technical and organisational conditions and measures

Ensure operatives are trained to minimise exposure	
--	--

Conditions and measures related to sewage treatment plant

No additional information	
---------------------------	--

Conditions and measures related to treatment of waste (including article waste)

See section 13 of the SDS	
---------------------------	--

Other conditions affecting environmental exposure

Closed systems are used in order to prevent unintended emissions	
--	--

2.2.2. Control of worker exposure: PROC4

PROC4	Use in batch and other process (synthesis) where opportunity for exposure arises
-------	--

Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	<= 100 %

Amount used (or contained in articles), frequency and duration of use/exposure

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.	
Exposure duration	<= 8 h/day
Covers frequency up to:	5 days/week

Technical and organisational conditions and measures

Handle product within a closed system	
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.	
Drain down and flush system prior to equipment break-in or maintenance.	
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.	

Ammonia, anhydrous

NOAL_0002

Country : FI / Language : EN

Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable face shield. Wear suitable coveralls to prevent exposure to the skin	Personal protection measures have to be applied in case of potential exposure only.
Wear gloves providing a minimum efficiency of (%):	90
Wear a respirator providing a minimum efficiency of	95 Mandatory if activities take place outdoors or indoors with no local exhaust ventilation
See section 8 of the SDS.	

Other conditions affecting workers exposure

Indoor or outdoor use	
-----------------------	--

2.2.3. Control of worker exposure: PROC8a

PROC8a	Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non dedicated facilities
--------	--

Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	<= 100 %

Amount used (or contained in articles), frequency and duration of use/exposure

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.	
Exposure duration	<= 8 h/day
Covers frequency up to:	5 days/week

Technical and organisational conditions and measures

Handle product within a closed system	
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.	
Drain down and flush system prior to equipment break-in or maintenance.	
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable face shield. Wear suitable coveralls to prevent exposure to the skin	Personal protection measures have to be applied in case of potential exposure only.
Wear gloves providing a minimum efficiency of (%):	90
Wear a respirator providing a minimum efficiency of	95 Mandatory if activities take place outdoors or indoors with no local exhaust ventilation
See section 8 of the SDS.	

Other conditions affecting workers exposure

Indoor or outdoor use	
-----------------------	--

2.3. Exposure estimation and reference to its source

2.3.1. Environmental release and exposure: ERC9a, ERC9b

Qualitative approach used to conclude safe use, The exposure of aquatic, terrestrial, sediment and sewage treatment microorganisms is considered to be negligible because the substance partitions primarily to air when released to the environment. The resulting environmental exposure is not expected to add significantly to already present background levels of the gas in the environment. An additional assessment for environmental exposure for wide dispersive uses has therefore not been presented in section 3.

2.3.2. Worker exposure: PROC4

Ammonia, anhydrous

NOAL_0002

Country : FI / Language : EN

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Dermal - Long-term - systemic effects	0.69 mg/kg bodyweight/day	Indoor use , With LEV, No gloves worn	0.101
	0.69 mg/kg bodyweight/day	Outdoor use, Indoor use , Without LEV, Gloves worn (90% Reduction)	0.101
Inhalation - Long-term - systemic effects	2.48 mg/m ³	Outdoor use, With RPE xx%95%	0.052
	7.08 mg/m ³	Indoor use , With LEV, No RPE	0.149
Dermal - Acute - systemic effects	0.69 mg/kg bodyweight/day	Indoor use , With LEV, No gloves worn	0.101
	0.69 mg/kg bodyweight/day	Outdoor use, Indoor use , Without LEV, Gloves worn (90% Reduction)	0.101
Inhalation - Acute - systemic effects	2.48 mg/m ³	Outdoor use, With RPE xx%95%	0.052
	7.08 mg/m ³	Indoor use , With LEV, No RPE	0.149
Acute - Local - Inhalation	2.48 mg/m ³	Outdoor use, With RPE xx%95%	0.069
	7.08 mg/m ³	Indoor use , With LEV, No RPE	0.197
Long term - Local - Inhalation	2.48 mg/m ³	Outdoor use, With RPE xx%95%	0.177
	7.08 mg/m ³	Indoor use , With LEV, No RPE	0.506

2.3.3. Worker exposure: PROC8a

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Dermal - Long-term - systemic effects	0.14 mg/kg bodyweight/day	Indoor use , With LEV, No gloves worn	0.021
	1.37 mg/kg bodyweight/day	Outdoor use, Indoor use , Without LEV, Gloves worn (90% Reduction)	0.201
Inhalation - Long-term - systemic effects	6.2 mg/m ³	Outdoor use, With RPE xx%95%	0.13
	0.89 mg/m ³	Indoor use , With LEV, No RPE	0.019
Dermal - Acute - systemic effects	0.14 mg/kg bodyweight/day	Indoor use , With LEV, No gloves worn	0.021
	1.37 mg/kg bodyweight/day	Outdoor use, Indoor use , Without LEV, Gloves worn (90% Reduction)	0.201
Inhalation - Acute - systemic effects	6.2 mg/m ³	Outdoor use, With RPE xx%95%	0.13
	0.89 mg/m ³	Indoor use , With LEV, No RPE	0.019
Acute - Local - Inhalation	6.2 mg/m ³	Outdoor use, With RPE xx%95%	0.172
	0.89 mg/m ³	Indoor use , With LEV, No RPE	0.025
Long term - Local - Inhalation	6.2 mg/m ³	Outdoor use, With RPE xx%95%	0.443
	0.89 mg/m ³	Indoor use , With LEV, No RPE	0.064

2.4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

2.4.1. Environment

Guidance - Environment	Check that RMMs and OCs are as described above or of equivalent efficiency
------------------------	--

2.4.2. Health

Guidance - Health	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see : http://www.ecetoc.org/tra
-------------------	--