

Phosphine

PHOSPHINE_100-SE



2.3 : Toxic gases



2.1 : Flammable gases



Environmentally
hazardous substances

Danger



SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : Phosphine , Fosfin N58
 SDS Nr : PHOSPHINE_100-SE replaces PHOSPHINE 100-SE 25 / 7 / 2014
 Chemical description : Phosphine
 CAS No : 7803-51-2
 EC No : 232-260-8
 Index No : 015-181-00-1
 Registration-No. : Registration deadline not expired.
 Chemical formula : PH₃

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional. Perform risk assessment prior to use.
 Test gas/Calibration gas. Laboratory use. Chemical reaction / Synthesis.
 Use for manufacture of electronic/photovoltaic components.
 Contact supplier for more information on uses.
 Uses advised against : Consumer use.

1.3. Details of the supplier of the safety data sheet

Company identification : AIR LIQUIDE GAS AB
 Lundavägen 151
 212 24 Malmö SWEDEN
 Tfn. 040 - 38 10 00, efter kontorstid 0220- 396 00
 E-Mail address)competent person) : Info.sweden@airliquide.com

1.4. Emergency telephone number

Emergency telephone number : 112

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

Hazard Class and Category Code Regulation EC 1272/2008)CLP)

• Health hazards : Acute toxicity, Inhalation - Category 1 - Danger - (CLP : Acute Tox. 1) - H330
 Skin corrosion - Category 1B - Danger - (CLP : Skin Corr. 1B) - H314
 Serious eye damage - Category 1 - Danger - (CLP : Eye Dam. 1) - H318
 • Physical hazards : Flammable gases - Category 1 - Danger - (CLP : Flam. Gas 1) - H220
 Gases under pressure - Liquefied gas - Warning - (CLP : Press. Gas) - H280

Phosphine

PHOSPHINE_100-SE

SECTION 2. Hazards identification (continued)

- **Environmental hazards** : Hazardous to the aquatic environment - Acute hazard - Category 1 - Warning - (CLP : Aquatic Acute 1) - H400

2.2. Label elements

Labelling Regulation EC 1272/2008 (CLP)

- **Hazard pictograms**



- **Hazard pictograms code** : GHS06 - GHS02 - GHS05 - GHS09 - GHS04
- **Signal word** : Danger
- **Hazard statements** : H220 - Extremely flammable gas.
H280 - Contains gas under pressure; may explode if heated.
H330 - Fatal if inhaled.
H314 - Causes severe skin burns and eye damage.
H400 - Very toxic to aquatic life.
- **Supplemental hazard information** : Spontaneously flammable in air.
: EUH071 supersedes H335 when assigned in the classification.
- **Precautionary statements**
 - **Prevention** : P260 - Do not breathe gas, vapours.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
P273 - Avoid release to the environment.
 - **Response** : P304+P340+P315 - IF INHALED : Remove person to fresh air and keep comfortable for breathing. Get immediate medical advice / attention.
P305+P351+P338+P315 - IF IN EYES : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice / attention.
P303+P361+P353+P315 - IF ON SKIN (or hair) : Take off immediately all contaminated clothing. Rinse skin with water/shower. Get immediate medical advice / attention.
P377 - Leaking gas fire : Do not extinguish, unless leak can be stopped safely.
P381 - Eliminate all ignition sources if safe to do so.
 - **Storage** : P403 - Store in a well-ventilated place.
P405 - Store locked up.

2.3. Other hazards

- : Spontaneously flammable in air.

SECTION 3. Composition/information on ingredients

3.1. Substance / 3.2. Mixture

Substance.

Substance name	Content [Vol-%]	CAS No	EC No	Index No	Registration No.	Classification
Phosphine	: 100 %	7803-51-2	232-260-8	015-181-00-1	* 2	Acute Tox. 1 (H330) Flam. Gas 1 (H220) Skin Corr. 1B (H314) Eye Dam 1 (H318) Press. Gas (Liq.) (H280) Aquatic Acute 1 (H400)

Contains no other components or impurities which will influence the classification of the product.

* 1: Listed in Annex IV / V REACH, exempted from registration.

* 2: Registration deadline not expired.

* 3: Registration not required: Substance manufactured or imported < 1t/y.

Full text of R-phrases see section 16. Full text of H-statements see section 16.

AIR LIQUIDE GAS AB

Lundavägen 151 212 24 Malmö SWEDEN

Tfn. 040 - 38 10 00, efter kontorstid 0220- 396 00

Phosphine**PHOSPHINE_100-SE****SECTION 3. Composition/information on ingredients)continued)****SECTION 4. First aid measures****4.1. Description of first aid measures**

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
- Skin contact : Remove contaminated clothing.
- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes.
- Ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

- : May cause severe chemical burns to skin and cornea. Suitable first-aid treatment should be immediately available. Seek medical advice before using product.
- Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.
- Delayed adverse effects possible.
- Refer to section 11.

4.3. Indication of any immediate medical attention and special treatment needed

- : Obtain medical assistance.

SECTION 5. Fire-fighting measures**5.1. Extinguishing media**

- Suitable extinguishing media : Shutting off the source of the gas is the preferred method of control.
Water spray or fog.
Dry powder.
- Unsuitable extinguishing media : Do not use water jet to extinguish.
Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

- Specific hazards** : Escaping gas cannot be extinguished.
Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products** : If involved in a fire the following toxic and/or corrosive fumes may be produced by thermal decomposition:
Phosphorus oxides/acids.

5.3. Advice for fire-fighters

- Specific methods** : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.
If possible, stop flow of product.
Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Extinguish any other fire.
Use water spray or fog to knock down fire fumes if possible.
Move containers away from the fire area if this can be done without risk.
- Special protective equipment for fire fighters** : Wear gas tight chemically protective clothing in combination with self contained breathing apparatus.
EN 943-2: Protective clothing against liquid and gaseous chemicals, aerosols and solid particles.
Gas-tight chemical protective suits for emergency teams.
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.

Phosphine**PHOSPHINE_100-SE****SECTION 5. Fire-fighting measures)continued)****SECTION 6. Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

- : Consider the risk of potentially explosive atmospheres.
- Try to stop release.
- Eliminate ignition sources.
- Evacuate area.
- Monitor concentration of released product.
- Ensure adequate air ventilation.
- Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.
- Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.
- Stay upwind.
- Act in accordance with local emergency plan.

6.2. Environmental precautions

- : Try to stop release.
- Reduce vapour with fog or fine water spray.

6.3. Methods and material for containment and cleaning up

- : Ventilate area.

6.4. Reference to other sections

- : See also sections 8 and 13.

SECTION 7. Handling and storage**7.1. Precautions for safe handling****Safe use of the product**

- : Consider pressure relief device(s) in gas installations.
- Only experienced and properly instructed persons should handle gases under pressure.
- The product must be handled in accordance with good industrial hygiene and safety procedures.
- Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.
- Avoid exposure, obtain special instructions before use.
- Take precautionary measures against static discharge.
- Purge air from system before introducing gas.
- Keep away from ignition sources (including static discharges).
- Do not smoke while handling product.
- Assess the risk of potentially explosive atmospheres and the need for explosion-proof equipment.
- Consider the use of only non-sparking tools.
- Ensure the complete gas system was (or is regularly) checked for leaks before use.
- Installation of a cross purge assembly between the cylinder and the regulator is recommended.
- Purge system with dry inert gas (e.g. helium or nitrogen) before gas is introduced and when system is placed out of service.
- Avoid suck back of water, acid and alkalis.
- Do not breathe gas.
- Avoid release of product into atmosphere.

Safe handling of the gas receptacle

- : Refer to supplier's container handling instructions.
- Do not allow backfeed into the container.
- Protect cylinders from physical damage; do not drag, roll, slide or drop.
- When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.
- Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.
- If user experiences any difficulty operating cylinder valve discontinue use and contact supplier.
- Never attempt to repair or modify container valves or safety relief devices.

Phosphine**PHOSPHINE_100-SE****SECTION 7. Handling and storage)continued)**

Damaged valves should be reported immediately to the supplier.
Keep container valve outlets clean and free from contaminants particularly oil and water.
Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.
Close container valve after each use and when empty, even if still connected to equipment.
Never attempt to transfer gases from one cylinder/container to another.
Never use direct flame or electrical heating devices to raise the pressure of a container.
Do not remove or deface labels provided by the supplier for the identification of the cylinder contents.

7.2. Conditions for safe storage, including any incompatibilities

: Keep container below 50°C in a well ventilated place.
Observe all regulations and local requirements regarding storage of containers.
Segregate from oxidant gases and other oxidants in store. Containers should be stored in the vertical position and properly secured to prevent them from falling over. Stored containers should be periodically checked for general condition and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. All electrical equipment in the storage areas should be compatible with the risk of a potentially explosive atmosphere.
Containers should not be stored in conditions likely to encourage corrosion. Keep away from combustible materials.

7.3. Specific end use(s)

: None.

SECTION 8. Exposure controls/personal protection**8.1. Control parameters****Occupational Exposure Limits**

Phosphine

- : ILV (EU) - 8 H - [mg/m³] : 0.15
- : ILV (EU) - 8 H - [ppm] : 0.1
- : ILV (EU) - 15 min - [mg/m³] : 0.28
- : ILV (EU) - 15 min - [ppm] : 0.2
- : TWA (SV) OEL 8h [ppm] : 0.3
- : TWA (SV) OEL 8h [mg/m³] : 0.4
- : Ceiling value (SV) OEL [ppm] : 1
- : Ceiling value (SV) OEL [mg/m³] : 1.4

DNEL: Derived no effect level)Workers)

Phosphine

- : Inhalation-short term (systemic) [mg/m³] : 0.28
- : Inhalation-long term (systemic) [mg/m³] : 0.14

PNEC: Predicted no effect concentration

: No data available.

8.2. Exposure controls

8.2.1. Appropriate engineering controls : Product to be handled in a closed system and under strictly controlled conditions.
Preferably use only permanent leak-tight installations (e.g. welded pipes).
Systems under pressure should be regularly checked for leakages.
Ensure exposure is below occupational exposure limits (where available).
Gas detectors should be used when toxic gases may be released.
Provide adequate general and local exhaust ventilation.
Consider work permit system e.g. for maintenance activities.

8.2.2. Individual protection measures, e.g. personal protective equipment : A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered:
PPE compliant to the recommended EN/ISO standards should be selected.
Protect eyes, face and skin from liquid splashes.

Phosphine

PHOSPHINE_100-SE

SECTION 8. Exposure controls/personal protection)continued)

- **Eye/face protection** : Wear safety glasses with side shields.
Wear goggles and a face shield when transfilling or breaking transfer connections.
Standard EN 166 - Personal eye-protection.
Provide readily accessible eye wash stations and safety showers.

 - **Skin protection**
 - **Hand protection** : Wear working gloves when handling gas containers.
Standard EN 388 - Protective gloves against mechanical risk.
Wear chemically resistant protective gloves.
Standard EN 374 - Protective gloves against chemicals.
The breakthrough time of the selected gloves must be greater than the intended use period.
Consult glove manufacturer's product information on material suitability and material thickness.

 - **Other** : Consider the use of flame resistant anti-static safety clothing.
Standard EN ISO 14116 - Limited flame spread materials.
Standard EN ISO 1149-5 - Protective clothing: Electrostatic properties.
Wear safety shoes while handling containers.
Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
Keep suitable chemically resistant protective clothing readily available for emergency use.
Standard EN943-1 - Full protective suits against liquid, solid and gaseous chemicals.

 - **Respiratory protection** : Gas filters may be used if all surrounding conditions e.g. type and concentration of the contaminant(s) and duration of use are known.
Use gas filters and full face mask, where exposure limits may be exceeded for a short-term period, e.g. connecting or disconnecting containers.
Recommended: Filter B (grey).
Consult respiratory device supplier's product information for the selection of the appropriate device.
Gas filters do not protect against oxygen deficiency.
Standard EN 14387 - Gas filter(s), combined filter(s) and full face mask - EN 136.
Keep self contained breathing apparatus readily available for emergency use.
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems.

 - **Thermal hazards** : None necessary.
- 8.2.3. Environmental exposure controls** : Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Appearance**
- Physical state at 20°C / 101.3kPa** : Gas.
- Colour** : Colourless.
- Odour** : Rotten fish. Poor warning properties at low concentrations.
Odour can persist.
Garlic like.
- Odour threshold** : Odour threshold is subjective and inadequate to warn for overexposure.
- pH value** : Not applicable for gases and gas-mixtures.
- Molar mass [g/mol]** : 34
- Melting point [°C]** : -134
- Boiling point [°C]** : -88
- Critical temperature [°C]** : 51.6
- Flash point [°C]** : Not applicable for gases and gas-mixtures.

Phosphine**PHOSPHINE_100-SE****SECTION 9. Physical and chemical properties)continued)**

Evaporation rate)ether=1)	: Not applicable for gases and gas-mixtures.
Flammability range [vol% in air]	: 1.6 - 100 Pyrophoric.
Vapour pressure [20°C]	: 34.6 bar
Relative density, gas %air=1%	: 1.2
Relative density, liquid %water=1%	: 0.74
Solubility in water [mg/l]	: 300
Partition coefficient n-octanol/water [log Kow]	: Not applicable for inorganic gases.
Auto-ignition temperature [°C]	: 38
Viscosity at 20°C [mPa.s]	: Not applicable.
Explosive Properties	: Not applicable.
Oxidising Properties	: None.

9.2. Other information

Other data	: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.
------------	--

SECTION 10. Stability and reactivity**10.1. Reactivity**

: No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

: Stable under normal conditions.

10.3. Possibility of hazardous reactions: Can form explosive mixture with air. Can ignite spontaneously in air (fire cannot be put out). Can form spontaneous, violently explosive mixture in air.
May react violently with oxidants.**10.4. Conditions to avoid**

: Keep away from heat, sparks, open flames, hot surfaces. – No smoking.

10.5. Incompatible materials: Air, Oxidiser.
For additional information on compatibility refer to ISO 11114.**10.6. Hazardous decomposition products**

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11. Toxicological information**11.1. Information on toxicological effects**

Acute toxicity	: Delayed fatal pulmonary oedema possible.
Rat inhalation LC50 [ppm/4h]	: 10
Skin corrosion/irritation	: Irritation to skin.
Serious eye damage/irritation	: Irritation to eyes.
Respiratory or skin sensitisation	: No known effects from this product.
Carcinogenicity	: No known effects from this product.

Phosphine**PHOSPHINE_100-SE****SECTION 11. Toxicological information)continued)**

Germ cell mutagenicity	: No known effects from this product.
Reproductive toxicity	: No known effects from this product.
STOT-single exposure	: Irritation to the respiratory tract. Damage to central nervous system.
STOT-repeated exposure	: No known effects from this product.
Aspiration hazard	: Not applicable for gases and gas-mixtures.

SECTION 12. Ecological information**12.1. Toxicity**

: Very toxic to aquatic life.

12.2. Persistence and degradability

: Not applicable for inorganic gases.

12.3. Bioaccumulative potential

: No ecological damage caused by this product.

12.4. Mobility in soil

: Because of its high volatility, the product is unlikely to cause ground or water pollution.

12.5. Results of PBT and vPvB assessment

: No data available.

12.6. Other adverse effects

Effect on the ozone layer	: May cause pH changes in aqueous ecological systems.
Effect on global warming	: None.
	: No known effects from this product.

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

: Must not be discharged to atmosphere.
Gas may be scrubbed in alkaline solution under controlled conditions to avoid violent reaction.
Toxic and corrosive gases formed during combustion should be scrubbed before discharge to atmosphere.
Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org> for more guidance on suitable disposal methods.
Ensure that the emission levels from local regulations or operating permits are not exceeded.
Consult supplier for specific recommendations.

**List of hazardous waste codes)from
Commission Decision 2001/118/EC)**

: 16 05 04: Gases in pressure containers (including halons) containing dangerous substances.

13.2. Additional information

: None.

Phosphine

PHOSPHINE_100-SE

SECTION 14. Transport information

UN number : 2199

Labelling ADR, IMDG, IATA



: 2.1 : Flammable gases
2.3 : Toxic gases
Environmentally hazardous substances

Transport by road/rail)ADR/RID)

Transport by air)ICAO-TI / IATA-DGR)

Transport by sea)IMDG)

Classification code : 2 TF

H.I. nr : --

Tunnel Restriction : D : Passage forbidden through tunnels of category D and E.

Emergency Schedule)EmS) - Fire : F-D

Emergency Schedule)EmS) - Spillage : S-U

14.6 Special precautions for user

Packing Instruction(s) : P200

Passenger and Cargo Aircraft : FORBIDDEN.

Cargo Aircraft only : FORBIDDEN.

Special precautions for user : Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.
Before transporting product containers:
- Ensure that containers are firmly secured.
- Ensure cylinder valve is closed and not leaking.
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure valve protection device (where provided) is correctly fitted.
- Ensure there is adequate ventilation.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not applicable.

UN proper shipping name : PHOSPHINE

Transport hazard class(es) : 2

Environmental hazards : Environmentally hazardous substance / mixture.

Proper shipping name : PHOSPHINE

Class : 2.3

Packing instruction : P200

IMDG-Marine pollutant : Marine pollutant.

Proper shipping name)IATA) : PHOSPHINE

Class : 2.3

Phosphine**PHOSPHINE_100-SE****SECTION 15. Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**EU legislation

Restrictions on use : None.

Seveso directive 2012/18/EC : Listed.

National legislation

National legislation : Ensure all national/local regulations are observed.

15.2. Chemical safety assessment

: This product is either exempt from REACH, does not meet the minimum volume threshold for a CSR or the CSA has not yet been carried out.

SECTION 16. Other information**Indication of changes** : Revised safety data sheet in accordance with commission regulation (EU) No 2015/830.**Training advice** : Ensure operators understand the flammability hazard.
Users of breathing apparatus must be trained.
Ensure operators understand the toxicity hazard.**List of full text of H-statements in section 3.** : H220 - Extremely flammable gas.
H280 - Contains gas under pressure; may explode if heated.
H314 - Causes severe skin burns and eye damage.
H318 - Causes serious eye damage.
H330 - Fatal if inhaled.
H400 - Very toxic to aquatic life.**Further information** : This Safety Data Sheet has been established in accordance with the applicable European Union legislation.**DISCLAIMER OF LIABILITY** : Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.
Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.**End of document**