

**Sulphur hexafluoride****SF6\_110-SE**

2.2 : Non-flammable, non-toxic gases

**Warning****SECTION 1. Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Trade name : Sulphur hexafluoride , SF6 N37, SF6 N47 Medicinsk  
SDS Nr : SF6\_110-SE replaces SF6 110-SE 25 / 7 / 2014  
Chemical description : Sulphur hexafluoride  
CAS No :2551-62-4  
EC No :219-854-2  
Index No :---  
Registration-No. : 01-2119458769-17-  
Chemical formula : SF6

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Relevant identified uses : Industrial and professional. Perform risk assessment prior to use.  
Test gas/Calibration gas. Laboratory use. Chemical reaction / Synthesis.  
Use for manufacture of electronic/photovoltaic components.  
Contact supplier for more information on uses.

Uses advised against : Do not inhale product on purpose because of the risk of asphyxiation.

**1.3. Details of the supplier of the safety data sheet**

Company identification : AIR LIQUIDE GAS AB  
Lundavägen 151  
212 24 Malmö SWEDEN  
Tfn. 040 - 38 10 00, efter kontorstid 0220- 396 00

E-Mail address (competent person) : Info.sweden@airliquide.com

**1.4. Emergency telephone number**

Emergency telephone number : 112

**SECTION 2. Hazards identification****2.1. Classification of the substance or mixture****Hazard Class and Category Code Regulation EC 1272/2008 (CLP)**

• Physical hazards : Gases under pressure - Liquefied gas - Warning - (CLP : Press. Gas) - H280

**2.2. Label elements****Labelling Regulation EC 1272/2008 (CLP)****AIR LIQUIDE GAS AB**

Lundavägen 151 212 24 Malmö SWEDEN  
Tfn. 040 - 38 10 00, efter kontorstid 0220- 396 00

## Sulphur hexafluoride

## SF6\_110-SE

### SECTION 2. Hazards identification (continued)

• Hazard pictograms



- Hazard pictograms code : GHS04
- Signal word : Warning
- Hazard statements : H280 - Contains gas under pressure; may explode if heated.
- Precautionary statements : P403 - Store in a well-ventilated place.

#### 2.3. Other hazards

- : Contact with liquid may cause cold burns/frostbite. Asphyxiant in high concentrations.

### SECTION 3. Composition/information on ingredients

#### 3.1. Substance / 3.2. Mixture

Substance.

Substance name	Content [Vol-%]	CAS No	EC No	Index No	Registration No.	Classification
Sulphur hexafluoride	100 %	2551-62-4	219-854-2	----	01-2119458769-17-	Press. Gas (Liq.) (H280)

Contains no other components or impurities which will influence the classification of the product.

\* 1: Listed in Annex IV / V REACH, exempted from registration.

\* 2: Registration deadline not expired.

\* 3: Registration not required: Substance manufactured or imported < 1t/y.

Full text of R-phrases see section 16. Full text of H-statements see section 16.

### SECTION 4. First aid measures

#### 4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
- Skin contact : In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.
- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes.
- Ingestion : Ingestion is not considered a potential route of exposure.

#### 4.2. Most important symptoms and effects, both acute and delayed

- : In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/ consciousness. Victim may not be aware of asphyxiation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

- : None.

**Sulphur hexafluoride****SF6\_110-SE****SECTION 5. Fire-fighting measures****5.1. Extinguishing media**

- Suitable extinguishing media : Water spray or fog.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

**5.2. Special hazards arising from the substance or mixture**

- Specific hazards** : Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products** : If involved in a fire the following toxic and/or corrosive fumes may be produced by thermal decomposition:  
Hydrogen fluoride.  
Sulphur dioxide.

**5.3. Advice for fire-fighters**

- Specific methods** : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.  
If possible, stop flow of product.  
Use water spray or fog to knock down fire fumes if possible.  
Move containers away from the fire area if this can be done without risk.
- Special protective equipment for fire fighters** : Use self-contained breathing apparatus.  
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.  
Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.  
Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters.

**SECTION 6. Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

- : Try to stop release.  
Monitor concentration of released product.  
Evacuate area.  
Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.  
Ensure adequate air ventilation.  
Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.  
Stay upwind.  
Act in accordance with local emergency plan.

**6.2. Environmental precautions**

- : Try to stop release.

**6.3. Methods and material for containment and cleaning up**

- : Ventilate area.

**6.4. Reference to other sections**

- : See also sections 8 and 13.

**Sulphur hexafluoride**

**SF6\_110-SE**

**SECTION 7. Handling and storage**

**7.1. Precautions for safe handling**

**Safe use of the product**

: Consider pressure relief device(s) in gas installations.  
 Only experienced and properly instructed persons should handle gases under pressure.  
 The product must be handled in accordance with good industrial hygiene and safety procedures.  
 Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.  
 Do not smoke while handling product.  
 Ensure the complete gas system was (or is regularly) checked for leaks before use.  
 Do not breathe gas.  
 Avoid release of product into atmosphere.

**Safe handling of the gas receptacle**

: Refer to supplier's container handling instructions.  
 Suck back of water into the container must be prevented.  
 Do not allow backfeed into the container.  
 Protect cylinders from physical damage; do not drag, roll, slide or drop.  
 When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.  
 Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.  
 If user experiences any difficulty operating cylinder valve discontinue use and contact supplier.  
 Never attempt to repair or modify container valves or safety relief devices.  
 Damaged valves should be reported immediately to the supplier.  
 Keep container valve outlets clean and free from contaminants particularly oil and water.  
 Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.  
 Close container valve after each use and when empty, even if still connected to equipment.  
 Never attempt to transfer gases from one cylinder/container to another.  
 Never use direct flame or electrical heating devices to raise the pressure of a container.  
 Do not remove or deface labels provided by the supplier for the identification of the cylinder contents.

**7.2. Conditions for safe storage, including any incompatibilities**

: Keep container below 50°C in a well ventilated place.  
 Observe all regulations and local requirements regarding storage of containers. Containers should be stored in the vertical position and properly secured to prevent them from falling over. Stored containers should be periodically checked for general condition and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition.  
 Containers should not be stored in conditions likely to encourage corrosion. Keep away from combustible materials.

**7.3. Specific end use(s)**

: None.

**SECTION 8. Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational Exposure Limits**

**Sulphur hexafluoride** : TWA (SV) OEL 8h [ppm] : 1000  
 : TWA (SV) OEL 8h [mg/m<sup>3</sup>] : 6000

**DNEL: Derived no effect level (Workers)**

**Sulphur hexafluoride** : Inhalation-long term (local) [mg/m<sup>3</sup>] : 77900  
 : Inhalation-long term (systemic) [mg/m<sup>3</sup>] : 77900

**PNEC: Predicted no effect concentration**

**Sulphur hexafluoride** : Aqua (freshwater) [mg/l] : 0.15

**Sulphur hexafluoride**

**SF6\_110-SE**

**SECTION 8. Exposure controls/personal protection )continued)**

: Aqua (marine water) [mg/l] : 1.5

**8.2. Exposure controls**

- 8.2.1. Appropriate engineering controls** : Systems under pressure should be regularly checked for leakages. Oxygen detectors should be used when asphyxiating gases may be released. Consider work permit system e.g. for maintenance activities. Provide adequate general and local exhaust ventilation. Ensure exposure is below occupational exposure limits (where available).
- 8.2.2. Individual protection measures, e.g. personal protective equipment** : A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered:  
PPE compliant to the recommended EN/ISO standards should be selected.
- **Eye/face protection** : Wear safety glasses with side shields.  
Wear safety glasses with side shields or goggles when transfilling or breaking transfer connections.  
Standard EN 166 - Personal eye-protection.
  - **Skin protection**
    - **Hand protection** : Wear working gloves when handling gas containers.  
Standard EN 388 - Protective gloves against mechanical risk.
    - **Other** : Wear safety shoes while handling containers.  
Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
  - **Respiratory protection** : Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres.  
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
  - **Thermal hazards** : None necessary.
- 8.2.3. Environmental exposure controls** : Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

**SECTION 9. Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Appearance	
Physical state at 20°C / 101.3kPa	: Gas.
Colour	: Colourless.
Odour	: No odour warning properties.
Odour threshold	: Odour threshold is subjective and inadequate to warn for overexposure.
pH value	: Not applicable for gases and gas-mixtures.
Molar mass [g/mol]	: 146
Melting point [°C]	: -50.8
Boiling point [°C]	: -64 (s)
Critical temperature [°C]	: 45.5
Flash point [°C]	: Not applicable for gases and gas-mixtures.
Evaporation rate )ether=1)	: Not applicable for gases and gas-mixtures.
Flammability range [vol% in air]	: Non flammable.
Vapour pressure [20°C]	: 21 bar
Relative density, gas %air=1%	: 5
Relative density, liquid %water=1%	: 1.4
Solubility in water [mg/l]	: 41
Partition coefficient n-octanol/water [log Kow]	: 1.68

**AIR LIQUIDE GAS AB**

Lundavägen 151 212 24 Malmö SWEDEN  
Tfn. 040 - 38 10 00, efter kontorstid 0220- 396 00

**Sulphur hexafluoride****SF6\_110-SE****SECTION 9. Physical and chemical properties )continued)**

Auto-ignition temperature [°C] : Not applicable.  
Viscosity at 20°C [mPa.s] : Not applicable.  
Explosive Properties : Not applicable.  
Oxidising Properties : None.

**9.2. Other information**

Other data : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

**SECTION 10. Stability and reactivity****10.1. Reactivity**

: No reactivity hazard other than the effects described in sub-sections below.

**10.2. Chemical stability**

: Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

: None.

**10.4. Conditions to avoid**

: None under recommended storage and handling conditions (see section 7).

**10.5. Incompatible materials**

: For additional information on compatibility refer to ISO 11114.

**10.6. Hazardous decomposition products**

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

**SECTION 11. Toxicological information****11.1. Information on toxicological effects**

Acute toxicity : No known toxicological effects from this product.  
Skin corrosion/irritation : No known effects from this product.  
Serious eye damage/irritation : No known effects from this product.  
Respiratory or skin sensitisation : No known effects from this product.  
Carcinogenicity : No known effects from this product.  
Germ cell mutagenicity : No known effects from this product.  
Reproductive toxicity : No known effects from this product.  
STOT-single exposure : No known effects from this product.  
STOT-repeated exposure : No known effects from this product.  
Aspiration hazard : Not applicable for gases and gas-mixtures.

**Sulphur hexafluoride****SF6\_110-SE****SECTION 12. Ecological information****12.1. Toxicity**

EC50 48h - Daphnia magna [mg/l] : 247  
EC50 72h Algae [mg/l] : No data available.  
LC50-96 h - fish [mg/l] : 236

**12.2. Persistence and degradability**

: Not applicable for inorganic gases.

**12.3. Bioaccumulative potential**

: No data available.

**12.4. Mobility in soil**

: Because of its high volatility, the product is unlikely to cause ground or water pollution.

**12.5. Results of PBT and vPvB assessment**

: Not classified as PBT or vPvB.

**12.6. Other adverse effects**

Effect on the ozone layer : None.  
Global warming potential [CO<sub>2</sub>=1] : 22800  
Effect on global warming : Contains fluorinated greenhouse gases.  
When discharged in large quantities may contribute to the greenhouse effect.

**SECTION 13. Disposal considerations****13.1. Waste treatment methods**

: Avoid discharge to atmosphere.  
Do not discharge into any place where its accumulation could be dangerous.  
Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org> for more guidance on suitable disposal methods.  
Ensure that the emission levels from local regulations or operating permits are not exceeded.  
Consult supplier for specific recommendations.

List of hazardous waste codes )from  
Commission Decision 2001/118/EC)

: 16 05 04: Gases in pressure containers (including halons) containing dangerous substances.

**13.2. Additional information**

: None.

**SECTION 14. Transport information**

UN number : 1080  
Labelling ADR, IMDG, IATA



: 2.2 : Non-flammable, non-toxic gases

Transport by road/rail )ADR/RID)  
Transport by air )ICAO-TI / IATA-DGR)  
Transport by sea )IMDG)

**AIR LIQUIDE GAS AB**

Lundavägen 151 212 24 Malmö SWEDEN  
Tfn. 040 - 38 10 00, efter kontorstid 0220- 396 00

**Sulphur hexafluoride**

**SF6\_110-SE**

**SECTION 14. Transport information )continued)**

Classification code : 2 A  
 H.I. nr : 20  
 Tunnel Restriction : C/E Tank carriage: Passage forbidden through tunnels of category C, D and E; Other carriage: Passage forbidden through tunnels of category E  
 Emergency Schedule )EmS) - Fire : F-C  
 Emergency Schedule )EmS) - Spillage : S-V

**14.6 Special precautions for user**

Packing Instruction(s) : P200  
 Passenger and Cargo Aircraft : Allowed.  
 Packing instruction - Passenger and Cargo Aircraft : 200  
 Cargo Aircraft only : Allowed.  
 Packing instruction - Cargo Aircraft only : 200  
 Special precautions for user : Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.  
 Before transporting product containers:  
 - Ensure that containers are firmly secured.  
 - Ensure cylinder valve is closed and not leaking.  
 - Ensure valve outlet cap nut or plug (where provided) is correctly fitted.  
 - Ensure valve protection device (where provided) is correctly fitted.  
 - Ensure there is adequate ventilation.  
 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not applicable.  
 UN proper shipping name : SULPHUR HEXAFLUORIDE  
 Transport hazard class(es) : 2  
 Environmental hazards : None.  
 Proper shipping name : SULPHUR HEXAFLUORIDE  
 Class : 2.2  
 Packing instruction : P200  
 IMDG-Marine pollutant : -  
 Proper shipping name )IATA) : SULPHUR HEXAFLUORIDE  
 Class : 2.2

**SECTION 15. Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

EU legislation

Restrictions on use : Not allowed for magnesium die casting in uses above 850 kg/y. (Regulation 842/2006).  
 Not allowed for inflating tyres. (Regulation 842/2006).  
 Seveso directive 2012/18/EC : Not covered.

National legislation

National legislation : Ensure all national/local regulations are observed.

**15.2. Chemical safety assessment**

: A CSA has been carried out.



**Sulphur hexafluoride****SF6\_110-SE****SECTION 16. Other information**

<b>Indication of changes</b>	: Revised safety data sheet in accordance with commission regulation (EU) No 2015/830.
<b>Training advice</b>	: The hazard of asphyxiation is often overlooked and must be stressed during operator training.
<b>List of full text of H-statements in section 3.</b>	: H280 - Contains gas under pressure; may explode if heated.
<b>Further information</b>	: This Safety Data Sheet has been established in accordance with the applicable European Union legislation.
<b>DISCLAIMER OF LIABILITY</b>	: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

**End of document**