

## Carbon monoxide

**NOAL\_0019**

Country : SE / Language : EN

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name : Carbon monoxide, Carbon monoxide N20, Kuliite, Carbon monoxide N47, Carbon monoxide N23

SDS no : NOAL\_0019

Chemical description : Carbon monoxide  
CAS-No. : 630-08-0  
EC-No. : 211-128-3  
EC Index-No. : 006-001-00-2

Registration-No. : 01-2119480165-39

Chemical formula : CO

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional uses. Perform risk assessment prior to use.  
See the list of identified uses and exposure scenarios in the annex of the safety data sheet.  
Contact supplier for more information on uses.

Uses advised against : Consumer use.

#### 1.3. Details of the supplier of the safety data sheet

##### Company identification

AIR LIQUIDE GAS AB  
Lundavägen 151  
21209 Malmö - SWEDEN  
T +46 40 38 10 00  
[eunordic-sds@airliquide.com](mailto:eunordic-sds@airliquide.com)

E-Mail address (competent person) : [eunordic-sds@airliquide.com](mailto:eunordic-sds@airliquide.com)

#### 1.4. Emergency telephone number

Emergency telephone number : 112  
Availability  
(24 / 7)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Physical hazards	Flammable gases, Category 1	H220
	Gases under pressure : Compressed gas	H280
Health hazards	Acute toxicity (inhalation:gas) Category 3	H331
	Reproductive toxicity, Category 1A	H360D
	Specific target organ toxicity — Repeated exposure, Category 1	H372

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) : Danger

Hazard statements (CLP) : H220 - Extremely flammable gas.

**Carbon monoxide****NOAL\_0019**

Country : SE / Language : EN

H280 - Contains gas under pressure; may explode if heated.  
H331 - Toxic if inhaled.  
H360D - May damage the unborn child.  
H372 - Causes damage to organs through prolonged or repeated exposure.

## Precautionary statements (CLP)

- Prevention : P202 - Do not handle until all safety precautions have been read and understood.  
P260 - Do not breathe gas, vapours.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Response : P308+P313 - IF exposed or concerned: Get medical advice.  
P304+P340+P315 - IF INHALED : Remove person to fresh air and keep comfortable for breathing. Get immediate medical advice.  
P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.  
P381 - In case of leakage, eliminate all ignition sources.
- Storage : P405 - Store locked up.  
P403 - Store in a well-ventilated place.

## Supplemental information

: Restricted to professional users.

**2.3. Other hazards**

: None.

**SECTION 3: Composition/information on ingredients****3.1. Substances**

Name	Product identifier	Composition [V-%]:	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Carbon monoxide	(CAS-No.) 630-08-0 (EC-No.) 211-128-3 (EC Index-No.) 006-001-00-2 (Registration-No.) 01-2119480165-39	100	Flam. Gas 1, H220 Press. Gas (Comp.), H280 Acute Tox. 3 (Inhalation:gas), H331 Repr. 1A, H360D STOT RE 1, H372

Contains no other components or impurities which will influence the classification of the product.

**3.2. Mixtures** : Not applicable.

**SECTION 4: First aid measures****4.1. Description of first aid measures**

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.  
Provide oxygen.
- Skin contact : Adverse effects not expected from this product.
- Eye contact : Adverse effects not expected from this product.
- Ingestion : Ingestion is not considered a potential route of exposure.

**4.2. Most important symptoms and effects, both acute and delayed**

: Symptoms may include dizziness, headache, nausea and loss of co-ordination.  
Delayed adverse effects possible.  
Refer to section 11.

**4.3. Indication of any immediate medical attention and special treatment needed**

: Obtain medical assistance.

**Carbon monoxide****NOAL\_0019**

Country : SE / Language : EN

**SECTION 5: Firefighting measures****5.1. Extinguishing media**

- Suitable extinguishing media : Water spray or fog.  
Dry powder.
- Unsuitable extinguishing media : Carbon dioxide.  
Do not use water jet to extinguish.

**5.2. Special hazards arising from the substance or mixture**

- Specific hazards : Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products : None that are more hazardous than the product itself.

**5.3. Advice for firefighters**

- Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.  
If possible, stop flow of product.  
Use water spray or fog to knock down fire fumes if possible.  
Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Extinguish any other fire.  
Move containers away from the fire area if this can be done without risk.
- Special protective equipment for fire fighters : Wear gas tight chemically protective clothing in combination with self contained breathing apparatus.  
Standard EN 943-2: Protective clothing against liquid and gaseous chemicals, aerosols and solid particles. Gas-tight chemical protective suits for emergency teams.  
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

- : Try to stop release.  
Evacuate area.  
Monitor concentration of released product.  
Consider the risk of potentially explosive atmospheres.  
Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.  
Eliminate ignition sources.  
Ensure adequate air ventilation.  
Act in accordance with local emergency plan.  
Stay upwind.

**6.2. Environmental precautions**

- : Try to stop release.

**6.3. Methods and material for containment and cleaning up**


- : Ventilate area.

**6.4. Reference to other sections**

- : See also sections 8 and 13.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

- Safe use of the product : Do not breathe gas.

	<b>SAFETY DATA SHEET</b>	Page : 4/16
		Revised edition no : 4.0
		Revision date : 2021-06-22
		Supersedes : 2020-07-15
<b>Carbon monoxide</b>		<b>NOAL_0019</b> Country : SE / Language : EN

Avoid release of product into atmosphere.

The product must be handled in accordance with good industrial hygiene and safety procedures.

Only experienced and properly instructed persons should handle gases under pressure.

Consider pressure relief device(s) in gas installations.

Ensure the complete gas system was (or is regularly) checked for leaks before use.

Do not smoke while handling product.

Avoid exposure, obtain special instructions before use.

Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.

Installation of a cross purge assembly between the container and the regulator is recommended.

Avoid suck back of water, acid and alkalis.

Assess the risk of potentially explosive atmospheres and the need for explosion-proof equipment.

Purge air from system before introducing gas.

Take precautionary measures against static discharge.

Keep away from ignition sources (including static discharges).

Consider the use of only non-sparking tools.

Ensure equipment is adequately earthed.

Safe handling of the gas receptacle

: Refer to supplier's container handling instructions.

Do not allow backfeed into the container.

Protect containers from physical damage; do not drag, roll, slide or drop.

When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.

Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.

If user experiences any difficulty operating valve discontinue use and contact supplier.

Never attempt to repair or modify container valves or safety relief devices.

Damaged valves should be reported immediately to the supplier.

Keep container valve outlets clean and free from contaminants particularly oil and water.

Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.

Close container valve after each use and when empty, even if still connected to equipment.

Never attempt to transfer gases from one cylinder/container to another.

Never use direct flame or electrical heating devices to raise the pressure of a container.

Do not remove or deface labels provided by the supplier for the identification of the content of the container.

Suck back of water into the container must be prevented.

Open valve slowly to avoid pressure shock.

**7.2. Conditions for safe storage, including any incompatibilities**

: Observe all regulations and local requirements regarding storage of containers.

Containers should not be stored in conditions likely to encourage corrosion.

Container valve guards or caps should be in place.

Containers should be stored in the vertical position and properly secured to prevent them from falling over.

Stored containers should be periodically checked for general condition and leakage.

Keep container below 50°C in a well ventilated place.

Store containers in location free from fire risk and away from sources of heat and ignition.

Keep away from combustible materials.

Segregate from oxidant gases and other oxidants in store.

All electrical equipment in the storage areas should be compatible with the risk of a potentially explosive atmosphere.

**7.3. Specific end use(s)**

: None.

## Carbon monoxide

### NOAL\_0019

Country : SE / Language : EN

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

<b>Carbon monoxide (630-08-0)</b>	
<b>EU - Occupational Exposure Limits</b>	
Local name	Carbon monoxide
IOELV TWA (mg/m <sup>3</sup> )	23 mg/m <sup>3</sup>
IOELV TWA (ppm)	20 ppm
IOELV STEL (mg/m <sup>3</sup> )	117 mg/m <sup>3</sup>
IOELV STEL (ppm)	100 ppm
Notes	SCOEL Recommendations (1995)
<b>Sweden - Occupational Exposure Limits</b>	
Local name	Avgaser som kolmonoxid
nivågränsvärde (NVG) (mg/m <sup>3</sup> )	25 mg/m <sup>3</sup> 25 mg/m <sup>3</sup> Avgaser 40 mg/m <sup>3</sup> Se även Avgaser
nivågränsvärde (NVG) (ppm)	20 ppm 20 ppm Avgaser 35 ppm Se även Avgaser
kortidsvärde (KTV) (mg/m <sup>3</sup> )	120 mg/m <sup>3</sup> Se även Avgaser
kortidsvärde (KTV) (ppm)	100 ppm Se även Avgaser
Anmärkning (SE)	5 (Tabellens särskilda gränsvärden för kvävedioxid och kolmonoxid är avsedda att ta hänsyn till den samlade effekten av de ämnen som förekommer i avgaser inklusive cancerframkallande ämnen. Dessa ämnen används alltså som indikatorsubstanser. Exponeringen ska vara godtagbar med hänsyn till båda värdena. Det är troligt att kolmonoxidvärdet blir dimensionerande vid exponering för avgaser från bensin- och gasol drivna motorer, medan kvävedioxidvärdet får motsvarande funktion för dieselavgaser. Däremot ska man inte räkna hygienisk effekt mellan kolmonoxid och kvävedioxid (se föreskrifterna om kemiska arbetsmiljörisiker))
<b>Carbon monoxide (630-08-0)</b>	
<b>EU - Occupational Exposure Limits</b>	
Local name	Carbon monoxide
IOELV TWA (mg/m <sup>3</sup> )	23 mg/m <sup>3</sup>
IOELV TWA (ppm)	20 ppm
IOELV STEL (mg/m <sup>3</sup> )	117 mg/m <sup>3</sup>
IOELV STEL (ppm)	100 ppm
Notes	SCOEL Recommendations (1995)
<b>Sweden - Occupational Exposure Limits</b>	
Local name	Avgaser som kolmonoxid
nivågränsvärde (NVG) (mg/m <sup>3</sup> )	25 mg/m <sup>3</sup> 25 mg/m <sup>3</sup> Avgaser 40 mg/m <sup>3</sup> Se även Avgaser
nivågränsvärde (NVG) (ppm)	20 ppm 20 ppm Avgaser 35 ppm Se även Avgaser
kortidsvärde (KTV) (mg/m <sup>3</sup> )	120 mg/m <sup>3</sup> Se även Avgaser
kortidsvärde (KTV) (ppm)	100 ppm Se även Avgaser
Anmärkning (SE)	5 (Tabellens särskilda gränsvärden för kvävedioxid och kolmonoxid är avsedda att ta hänsyn till den samlade effekten av de ämnen som förekommer i avgaser inklusive cancerframkallande ämnen. Dessa ämnen används alltså som indikatorsubstanser. Exponeringen ska vara godtagbar med hänsyn till båda värdena. Det är troligt att kolmonoxidvärdet blir dimensionerande vid exponering för avgaser från bensin- och gasol drivna motorer, medan kvävedioxidvärdet får motsvarande funktion för dieselavgaser. Däremot ska man inte räkna hygienisk effekt mellan kolmonoxid och kvävedioxid (se föreskrifterna om kemiska arbetsmiljörisiker))

<b>Carbon monoxide (630-08-0)</b>	
DNEL: Derived no effect level (Workers)	
Acute - local effects, inhalation	100 ppm
Acute - systemic effects, inhalation	100 ppm

## Carbon monoxide

**NOAL\_0019**

Country : SE / Language : EN

Long-term - local effects, inhalation	20 ppm
Long-term - systemic effects, inhalation	20 ppm

<b>Carbon monoxide (630-08-0)</b>	
DNEL: Derived no effect level (Workers)	
Acute - local effects, inhalation	100 ppm
Acute - systemic effects, inhalation	100 ppm
Long-term - local effects, inhalation	20 ppm
Long-term - systemic effects, inhalation	20 ppm

PNEC (Predicted No-Effect Concentration) : None established.

### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

- : Product to be handled in a closed system and under strictly controlled conditions.
- Provide adequate general and local exhaust ventilation.
- Preferably use permanent leak-tight installations (e.g. welded pipes).
- Systems under pressure should be regularly checked for leakages.
- Ensure exposure is below occupational exposure limits (where available).
- Gas detectors should be used when toxic gases may be released.
- Consider the use of a work permit system e.g. for maintenance activities.

#### 8.2.2. Individual protection measures, e.g. personal protective equipment

- : A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered:  
PPE compliant to the recommended EN/ISO standards should be selected.
- Eye/face protection : Wear safety glasses with side shields.  
Standard EN 166 - Personal eye-protection - specifications.
- Skin protection
  - Hand protection : Wear working gloves when handling gas containers.  
Standard EN 388 - Protective gloves against mechanical risk.
  - Other : Consider the use of flame resistant anti-static safety clothing.  
Standard EN ISO 14116 - Limited flame spread materials.  
Standard EN 1149-5 - Protective clothing: Electrostatic properties.  
Wear safety shoes while handling containers.  
Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
- Respiratory protection : Never use any kind of filtering respiratory protection equipment when working with this substance due to it having poor or no warning properties.  
Keep self contained breathing apparatus readily available for emergency use.  
Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems.  
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
- Thermal hazards : None in addition to the above sections.

#### 8.2.3. Environmental exposure controls

- : Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

- Physical state at 20°C / 101.3kPa : Gas
- Colour : Colourless.

**Carbon monoxide****NOAL\_0019**

Country : SE / Language : EN

Odour	: Odourless.
Odour threshold	: Odour threshold is subjective and inadequate to warn of overexposure.
pH	: Not applicable for gases and gas mixtures.
Melting point / Freezing point	: -205 °C
Boiling point	: -192 °C
Flash point	: Not applicable for gases and gas mixtures.
Evaporation rate	: Not applicable for gases and gas mixtures.
Flammability (solid, gas)	: Extremely flammable gas
Explosive limits	: 10.9 - 76 vol %
Vapour pressure [20°C]	: Not applicable.
Vapour pressure [50°C]	: Not applicable.
Vapour density	: Not applicable.
Relative density, liquid (water=1)	: 0.79
Relative density, gas (air=1)	: 1
Water solubility	: 30 mg/l
Partition coefficient n-octanol/water (Log Kow)	: 1.78
Auto-ignition temperature	: 605 °C
Decomposition temperature	: Not applicable.
Viscosity	: No reliable data available.
Explosive properties	: Not applicable.
Oxidising properties	: Not applicable.

**9.2. Other information**

Molar mass	: 28 g/mol
Critical temperature [°C]	: -140 °C

**SECTION 10: Stability and reactivity****10.1. Reactivity**

: No reactivity hazard other than the effects described in sub-sections below.

**10.2. Chemical stability**

: Stable under normal conditions.

**10.3. Possibility of hazardous reactions**: Can form explosive mixture with air.  
May react violently with oxidants.**10.4. Conditions to avoid**: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.  
Avoid moisture in installation systems.**10.5. Incompatible materials**: Air, Oxidisers.  
For additional information on compatibility refer to ISO 11114.  
See also 'EIGA Doc.95: Avoidance of Failure of CO and of CO/CO2 Mixtures Cylinders' at [www.eiga.eu](http://www.eiga.eu).**10.6. Hazardous decomposition products**

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Carbon monoxide

NOAL\_0019

Country : SE / Language : EN

**SECTION 11: Toxicological information****11.1. Information on toxicological effects**

Acute toxicity : Toxic if inhaled.

LC50 Inhalation - Rat [ppm]	3760 ppm/1h 1300 ppm/4h
-----------------------------	----------------------------

<b>Carbon monoxide (630-08-0)</b>	
LC50 Inhalation - Rat [ppm]	3760 ppm/1h 1300 ppm/4h

**Skin corrosion/irritation** : No known effects from this product.  
**Serious eye damage/irritation** : No known effects from this product.  
**Respiratory or skin sensitisation** : No known effects from this product.  
**Germ cell mutagenicity** : No known effects from this product.  
**Carcinogenicity** : No known effects from this product.  
**Reproductive toxicity** :  
Toxic for reproduction : Fertility : No known effects from this product.  
Toxic for reproduction : unborn child : May damage the unborn child.  
**STOT-single exposure** : Suppresses the oxygen uptake by red blood cells.  
**Target organ(s)** : Blood.  
**STOT-repeated exposure** : Causes damage to organs through prolonged or repeated exposure.  
**Target organ(s)** : heart.  
**Aspiration hazard** : Not applicable for gases and gas mixtures.

**SECTION 12: Ecological information****12.1. Toxicity**

Assessment : No ecological damage caused by this product.

EC50 48h - Daphnia magna [mg/l] : Study scientifically unjustified.

EC50 72h - Algae [mg/l] : Study scientifically unjustified.

LC50 96 h - Fish [mg/l] : Study scientifically unjustified.

<b>Carbon monoxide (630-08-0)</b>	
EC50 48h - Daphnia magna [mg/l]	Study scientifically unjustified.
EC50 72h - Algae [mg/l]	Study scientifically unjustified.
LC50 96 h - Fish [mg/l]	Study scientifically unjustified.

**12.2. Persistence and degradability**Assessment : Will not undergo hydrolysis.  
Not readily biodegradable.**12.3. Bioaccumulative potential**Assessment : Not expected to bioaccumulate due to the low log Kow (log Kow < 4).  
Refer to section 9.**12.4. Mobility in soil**Assessment : Because of its high volatility, the product is unlikely to cause ground or water pollution.  
Partition into soil is unlikely.**12.5. Results of PBT and vPvB assessment**

Assessment : Not classified as PBT or vPvB.



**Carbon monoxide****NOAL\_0019**

Country : SE / Language : EN

**12.6. Other adverse effects**

Other adverse effects : No known effects from this product.  
Effect on the ozone layer : None.  
Effect on global warming : Contains greenhouse gas(es).

**SECTION 13: Disposal considerations****13.1. Waste treatment methods**

Contact supplier if guidance is required.  
Do not discharge into areas where there is a risk of forming an explosive mixture with air.  
Waste gas should be flared through a suitable burner with flash back arrestor.  
Must not be discharged to atmosphere.  
Ensure that the emission levels from local regulations or operating permits are not exceeded.  
Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org> for more guidance on suitable disposal methods.  
Return unused product in original container to supplier.  
List of hazardous waste codes (from Commission Decision 2000/532/EC as amended) : 16 05 04 \*: Gases in pressure containers (including halons) containing hazardous substances.

**13.2. Additional information**

: External treatment and disposal of waste should comply with applicable local and/or national regulations.

**SECTION 14: Transport information****14.1. UN number**

UN-No. : 1016

**14.2. UN proper shipping name**

**Transport by road/rail (ADR/RID)** : CARBON MONOXIDE, COMPRESSED  
**Transport by air (ICAO-TI / IATA-DGR)** : Carbon monoxide, compressed  
**Transport by sea (IMDG)** : CARBON MONOXIDE, COMPRESSED

**14.3. Transport hazard class(es)****Labelling**

2.3 : Toxic gases.  
2.1 : Flammable gases.

**Transport by road/rail (ADR/RID)**

Class : 2  
Classification code : 1TF  
Hazard identification number : 263  
Tunnel Restriction : B/D - Tank carriage : Passage forbidden through tunnels of category B, C, D and E. Other carriage : Passage forbidden through tunnels of category D and E

**Transport by sea (IMDG)**

Class / Div. (Sub. risk(s)) : 2.3 (2.1)  
Emergency Schedule (EmS) - Fire : F-D  
Emergency Schedule (EmS) - Spillage : S-U

**Carbon monoxide****NOAL\_0019**

Country : SE / Language : EN

**14.4. Packing group**

Transport by road/rail (ADR/RID) : Not established.  
Transport by air (ICAO-TI / IATA-DGR) : Not established.  
Transport by sea (IMDG) : Not established.

**14.5. Environmental hazards**

Transport by road/rail (ADR/RID) : None.  
Transport by air (ICAO-TI / IATA-DGR) : None.  
Transport by sea (IMDG) : None.

**14.6. Special precautions for user****Packing Instruction(s)**

Transport by road/rail (ADR/RID) : P200  
Transport by air (ICAO-TI / IATA-DGR)  
Passenger and Cargo Aircraft : Forbidden.  
Cargo Aircraft only : Forbidden.  
Transport by sea (IMDG) : P200

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment.  
Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.  
Before transporting product containers:  
- Ensure there is adequate ventilation.  
- Ensure that containers are firmly secured.  
- Ensure valve is closed and not leaking.  
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.  
- Ensure valve protection device (where provided) is correctly fitted.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

: Not applicable.

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU-Regulations**

Restrictions on use : Restricted to professional users (Annex XVII REACH).  
Seveso Directive : 2012/18/EU (Seveso III) : Covered.

**National regulations**

National legislation : Ensure all national/local regulations are observed.

**15.2. Chemical safety assessment**

: A CSA has been carried out.

**SECTION 16: Other information**

Indication of changes : Revised safety data sheet in accordance with commission regulation (EU) No 453/2010.

## Carbon monoxide

### NOAL\_0019

Country : SE / Language : EN

**Abbreviations and acronyms**

: ATE - Acute Toxicity Estimate  
 CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008  
 REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006  
 EINECS - European Inventory of Existing Commercial Chemical Substances  
 CAS# - Chemical Abstract Service number  
 PPE - Personal Protection Equipment  
 LC50 - Lethal Concentration to 50 % of a test population  
 RMM - Risk Management Measures  
 PBT - Persistent, Bioaccumulative and Toxic  
 vPvB - Very Persistent and Very Bioaccumulative  
 STOT- SE : Specific Target Organ Toxicity - Single Exposure  
 CSA - Chemical Safety Assessment  
 EN - European Standard  
 UN - United Nations  
 ADR - International Agreement concerning the International Carriage of Dangerous Goods by Road  
 IATA - International Air Transport Association  
 IMDG code - International Maritime Dangerous Goods  
 RID - Regulations concerning the International Carriage of Dangerous Goods by Rail  
 WGK - Water Hazard Class  
 STOT - RE : Specific Target Organ Toxicity - Repeated Exposure

**Training advice**

: Ensure operators understand the flammability hazard.  
 Users of breathing apparatus must be trained.  
 Ensure operators understand the toxicity hazard.

**Full text of H- and EUH-statements**

Acute Tox. 3 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 3
Flam. Gas 1	Flammable gases, Category 1
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Repr. 1A	Reproductive toxicity, Category 1A
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
H220	Extremely flammable gas
H280	Contains gas under pressure; may explode if heated
H331	Toxic if inhaled.
H360D	May damage the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.

**Full text of use descriptors**

ERC2	Formulation of preparations
ERC6a	Industrial use resulting in manufacture of another substance (use of intermediates)
ERC6b	Industrial use of reactive processing aids
ERC8d	Wide dispersive outdoor use of processing aids in open systems
PROC1	Use in closed process, no likelihood of exposure
PROC2	Use in closed, continuous process with occasional controlled exposure
PROC3	Use in closed batch process (synthesis or formulation)
PROC4	Use in batch and other process (synthesis) where opportunity for exposure arises
PROC8b	Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities
PROC9	Transfer of substance or mixture into small containers (dedicated filling line, including weighing)
SU14	Manufacture of basic metals, including alloys
SU15	Manufacture of fabricated metal products, except machinery and equipment

**Carbon monoxide****NOAL\_0019**

Country : SE / Language : EN

SU3


Industrial uses: Uses of substances as such or in preparations\* at industrial sites

## DISCLAIMER OF LIABILITY

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

Details given in this document are believed to be correct at the time of going to press.

Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

	<b>SAFETY DATA SHEET</b>	Page : 13/16
		Revised edition no : 4.0
		Revision date : 2021-06-22
		Supersedes : 2020-07-15
<b>Carbon monoxide</b>		<b>NOAL_0019</b> Country : SE / Language : EN

**Annex to the safety data sheet**

This Annex documents the Exposure Scenarios (ESs) related to the identified uses of the registered substance. The ESs detail protective measures for workers and the environment in addition to those described in sections 7, 8, 11, 12 and 13 of the SDS that are required to ensure that the potential exposure to workers and the environment remains within acceptable levels for each of the identified uses.

**Table of contents of the Annex**

Identified Uses	Es N°	Short title	Page
Formulation of mixtures in pressure receptacles	EIGA01 9-1	Industrial uses, closed contained conditions	14
Metal treatment	EIGA01 9-1	Industrial uses, closed contained conditions	14
Electronic component manufacture	EIGA01 9-1	Industrial uses, closed contained conditions	14
Manufacture of pharmaceutical products	EIGA01 9-1	Industrial uses, closed contained conditions	14
Intermediate (transported, on-site isolated)	EIGA01 9-1	Industrial uses, closed contained conditions	14
Transfilling in pressure receptacles	EIGA01 9-1	Industrial uses, closed contained conditions	14
Feedstock in chemical processes	EIGA01 9-1	Industrial uses, closed contained conditions	14
Controlling agent in catalytic reaction	EIGA01 9-1	Industrial uses, closed contained conditions	14
Monomer in polymer production	EIGA01 9-1	Industrial uses, closed contained conditions	14
Calibration of analysis equipment	EIGA01 9-1	Industrial uses, closed contained conditions	14

## Carbon monoxide

**NOAL\_0019**

Country : SE / Language : EN

### 1. EIGA019-1: Industrial uses, closed contained conditions

#### 1.1. Title section

##### Industrial uses, closed contained conditions

 ES Ref.: EIGA019-1  
 Revision date: 01/09/2016

Processes, tasks, activities covered	Industrial uses, including product transfers and associated laboratory activities within different closed or contained systems
Environment	Use descriptors
CS1	ERC2, ERC6a, ERC6b, ERC8d
Worker	Use descriptors
CS2	PROC1
CS3	PROC2, PROC3, PROC4
CS4	PROC8b, PROC9
Assessment method	ECETOC TRA 2.0

#### 1.2. Conditions of use affecting exposure

##### 1.2.1. Control of environmental exposure: ERC2, ERC6a, ERC6b, ERC8d

ERC2	Formulation of preparations
ERC6a	Industrial use resulting in manufacture of another substance (use of intermediates)
ERC6b	Industrial use of reactive processing aids
ERC8d	Wide dispersive outdoor use of processing aids in open systems

##### Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	<= 100 %

##### Amount used, frequency and duration of use (or from service life)

The actual tonnage handled per site is not considered to influence the immissions as such for this scenario as there is practically no release	
Covers frequency up to:	5 days/week
Emission Days (days/year)	220

##### Technical and organisational conditions and measures

Wastewater emission controls are not applicable as there is no direct release to wastewater	
Soil emission controls are not applicable as there is no direct release to soil	
Ensure operatives are trained to minimise releases	

##### Conditions and measures related to sewage treatment plant

Not applicable as there is no release to wastewater	
---	--

##### Conditions and measures related to treatment of waste (including article waste)

External treatment and disposal of waste should comply with applicable local and/or national regulations	
See section 13 of the SDS	

##### Other conditions affecting environmental exposure

No additional information	
---------------------------	--

##### 1.2.2. Control of worker exposure: PROC1

PROC1	Use in closed process, no likelihood of exposure
-------	--

##### Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	<= 100 %

##### Amount used (or contained in articles), frequency and duration of use/exposure

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and	
--	--

## Carbon monoxide

**NOAL\_0019**

Country : SE / Language : EN

level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.	
Exposure duration	<= 8 h/day
Covers frequency up to:	5 days/week

<b>Technical and organisational conditions and measures</b>	
Handle product within a closed system	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems.	
See section 8 of the SDS.	

<b>Other conditions affecting workers exposure</b>	
Indoor or outdoor use	

### 1.2.3. Control of worker exposure: PROC2, PROC3, PROC4

PROC2	Use in closed, continuous process with occasional controlled exposure
PROC3	Use in closed batch process (synthesis or formulation)
PROC4	Use in batch and other process (synthesis) where opportunity for exposure arises

<b>Product (article) characteristics</b>	
Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	<= 100 %

<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.	
Exposure duration	<= 8 h/day
Covers frequency up to:	5 days/week

<b>Technical and organisational conditions and measures</b>	
Handle product within a closed system	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems.	
See section 8 of the SDS.	

<b>Other conditions affecting workers exposure</b>	
Indoor or outdoor use	

### 1.2.4. Control of worker exposure: PROC8b, PROC9

PROC8b	Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities
PROC9	Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

<b>Product (article) characteristics</b>	
Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	<= 100 %

<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the	

## Carbon monoxide

### NOAL\_0019

Country : SE / Language : EN

process-intrinsic emission potential.	
Exposure duration	<= 8 h/day
Covers frequency up to:	5 days/week

Technical and organisational conditions and measures	
Handle product within a closed system	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

Conditions and measures related to personal protection, hygiene and health evaluation	
Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems.	

Other conditions affecting workers exposure	
Indoor or outdoor use	

### 1.3. Exposure estimation and reference to its source

#### 1.3.1. Environmental release and exposure: ERC2, ERC6a, ERC6b, ERC8d

The exposure of aquatic, terrestrial, sediment and sewage treatment microorganisms is considered to be negligible because the substance partitions primarily to air when released to the environment. The resulting environmental exposure is not expected to add significantly to already present background levels of the gas in the environment

#### 1.3.2. Worker exposure: PROC1

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Inhalation - Long-term - systemic effects	0.011 mg/m <sup>3</sup>	Indoor use , With LEV	< 0.01
Inhalation - Acute - systemic effects	0.023 mg/m <sup>3</sup>	Indoor use , With LEV	< 0.001

#### 1.3.3. Worker exposure: PROC2, PROC3, PROC4

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Inhalation - Long-term - systemic effects	11.7 mg/m <sup>3</sup>	Indoor use , With LEV	0.585
	11.7 mg/m <sup>3</sup>	Indoor use , Without LEV	0.585
Inhalation - Acute - systemic effects	23.4 mg/m <sup>3</sup>	Indoor use , With LEV	0.234
	23.4 mg/m <sup>3</sup>	Indoor use , Without LEV	0.234

#### 1.3.4. Worker exposure: PROC8b, PROC9

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Inhalation - Long-term - systemic effects	23.3 mg/m <sup>3</sup>	Indoor use , With LEV	1.165
	23.3 mg/m <sup>3</sup>	Indoor use , Without LEV	1.165
Inhalation - Acute - systemic effects	46.7 mg/m <sup>3</sup>	Indoor use , With LEV	0.467
	46.7 mg/m <sup>3</sup>	Indoor use , Without LEV	0.467

### 1.4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

#### 1.4.1. Environment

Guidance - Environment	Check that RMMs and OCs are as described above or of equivalent efficiency
------------------------	--

#### 1.4.2. Health

Guidance - Health	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see : <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>
-------------------	--